

Ball Valves

BF, BFH, BG, BH, BO, BP, BR, BRC,
BV, BK and BU Series

Ball Valves
Plug Valves



Contents

Trunnion Ball Valves

BF and BFH Series



B-04

3-Piece Ball Valves

BG Series



B-11

3-Piece Ball Valves

BH Series



B-16

One-Piece Instrumentation Ball Valves

BO Series



B-25

Bar Stock Ball Valves

BP Series



B-38

Hex Bar Stock Ball Valves

BR Series



B-46

Hex Bar Stock Ball Valves

BRC Series



B-51

High Performance Ball Valves

BV Series



B-57

High Temperature Metal-Seated Ball Valves

BK Series



B-67

Alternative Fuel Service (AFS) Ball Valves

BU Series



B-71

Important Information about Ball Valves

- ⦿ FITOK ball valves are designed to be used in fully open or fully closed position.
- ⦿ Packing adjustment may be required during the service life of the valve (except for BF, BFH and BU series).
- ⦿ For better quality maintenance, FITOK ball valves should be kept in fully open position in warehouse.
- ⦿ Valves that have not been actuated for a period of time may have a higher initial actuation torque.

Trunnion Ball Valves

BF and BFH Series



Features

- ⦿ Maximum working pressures:
BF Series: 6,000 psig (414 bar)
BFH Series: 10,000 psig (690 bar)
- ⦿ Working temperature: 0°F to 450°F (-18°C to 232°C)
- ⦿ Compact, maximum-flow design with Cv up to 1.6
- ⦿ No packing adjustment required
- ⦿ Trunnion-style ball design prevents ball blowout for enhanced safety
- ⦿ Blowout-proof stem minimizes failures caused by stem movement or looseness
- ⦿ Disc-spring-loaded seats compensate for seat wear and pressure/temperature changes, improving leak-tight integrity
- ⦿ Available in 2-way or 3-way flow patterns
- ⦿ Each valve is factory leak-tested with nitrogen or compressed air at rated pressure
- ⦿ Low-temperature service option available
- ⦿ Available with ECE R110 type approval




Pressure vs. Temperature

BF Series



BFH Series

316 SS Body





Pressure Rating@100°F (38°C)

Material	End Connection	Pressure Rating, psig (bar)
316 SS	FNS2, FNS4 FL4, ML6	10000 (690)
	ML10	8400 (578)
	FL6/ML8	7500 (516)
	FL8	6700 (461)
	ML12	6800 (470)

Note: Maximum working pressure of BFH Series ball valves is 10,000 psig. The specified pressure rating is restricted by end connections.

Standard Materials of Construction

BF Series





Notes: Wetted components are listed in italics.

1. Ball trunnions are PTFE coated for BF series 2-way valves.
2. For other materials, please contact FITOK Group or our authorized distributors.

Item	Component	Valve Body Material			
		316 SS		Alloy 400	
		2-way	3-way	2-way	3-way
		Material Grade/ASTM Specification			
1	Handle	Nylon with SS insert			
2	Panel Nut	316 SS/A479			
3	Body	F316 SS/A182		Alloy 400/B164	
4	End Connection	316 SS/A479		Alloy 400/B164	
5	Seat Retainer Backup Ring	Reinforced PTFE			
6	Seat Retainer O-ring	FKM			
7	Seat Retainer Guide	316 SS/A479		Alloy 400/B164	
8	End Connection Seal	Silver-plated 316L/A269			
9	Trunnion O-ring	FKM	—	FKM	—
10	Trunnion Backup Ring	Reinforced PTFE	—	Reinforced PTFE	—
11	Trunnion Bearing	—	PEEK	—	PEEK
12	Ball	316 SS/A479	S21800/A479	Alloy 400/B164	
13	Seat Spring	Alloy X-750/AMS 5542			
14	Seat Retainer	316 SS/A479		Alloy 400/B164	
15	Seat	PTFE or PEEK or PCTFE			
16	Stem	316 SS/A479		Alloy 400/B164	
17	Stem Washer	PEEK			
18	Stem O-ring	FKM		FKM	
19	Secondary Stem Backup Ring	—	PTFE/D1710	—	PTFE/D1710
20	Primary Stem Backup Ring	—	PEEK	—	PEEK
21	Stop Pin	SS			
22	Set Screw	Zinc-plated carbon steel			
Lubricants		Fluorinated-based			

BFH Series







Item	Component	2-way	3-way
		Material Grade/ASTM Specification	
1	Handle	Nylon with SS insert	
2	Panel Nut	316 SS/A479	
3	Body	316 SS/A479	
4	End Connection	316 SS/A479	
5	Seat Retainer Backup Ring	Reinforced PTFE	
6	Seat Retainer O-ring	FKM	
7	Seat Retainer Guide	316 SS/A479	
8	End Connection Seal	Silver-plated 316L/A269	
9	Plug	316 SS/A479	
10	Ball	S21800/A479	
11	Seat Spring	Alloy X-750/AMS 5542	
12	Seat Retainer	316 SS/A479	
13	Seat	PEEK	
14	Stem	316 SS/A479	
15	Stem Washer	PEEK	
16	Stem O-ring	FKM	
17	Secondary Stem Backup Ring	PTFE/D1710	
18	Primary Stem Backup Ring	PEEK	
19	Stop Pin	SS	
20	Set Screw	Zinc-plated carbon steel	
Lubricants		Fluorinated-based	


Notes: Wetted components are listed in italics.
1. Ball trunnions are PTFE coated for BFH series ball valves.
2. For other materials, please contact FITOK Group or our authorized distributors.

Dimensions

2-way Valves



3-way Valves



1. FITOK means FITOK double ferrule tube fittings.
2. Sizes and types listed are standard. Other sizes and types are available upon request, please contact FITOK Group or our authorized distributors.
3. Dimensions are shown with tube fitting nuts finger-tightened. All dimensions are for reference only and are subject to change.
For dimensions not shown above, please contact FITOK Group or our authorized distributors.
4. Bottom port of all 3-way valves is 1/4 in. female NPT.

Special Application Ball Valves

Low-Temperature Service

BF and BFH series ball valves for low-temperature service, with a temperature rating of -40°F to 200°F (-40°C to 93°C), are available.

Low-temperature service valves have low-temperature NBR O-rings. All other materials are the same as those of standard valves.

To order a valve for low-temperature service, add -LT into the valve ordering number.


For example: BFSS-FL4-P-LT

BFSS-FL4-P-3-LT


Seal kit for field replacement is available, see "Seal Kits" on Page B-09.

Low-Temperature Service BF Series Pressure vs. Temperature

316 SS Body




Alloy 400 Body



Low-Temperature Service BFH Series Pressure vs. Temperature

316 SS Body



Note: The maximum working pressure for BFH series low-temperature service ball valves is the same as that of standard ball valves.


"Fast Fill" CNG Filling Station Application

BF series 3-way valves for use in "fast-fill" CNG filling station as well as a variety of filling station applications are available.

Features

- ⦿ A directional installation with 90 degree actuation for ease of operation during filling
 - ⦿ 3-way design with vent port for ease of venting after fill
 - ⦿ PEEK seats to reduce maintenance required in high-cycle applications
 - ⦿ Cycle life test report available upon request
 - ⦿ Field repairable with seal kit, see "Seal Kits" on Page B-09
- To order, the flow pattern designator should be specified as "3DL" in the valve ordering number.

Example: BFSS-FNS4-P-3DL (The material and pressure vs. temperature curve are the same with those of BF series standard valves.)
 BFSS-FNS4-P-3DL-LT (The material and pressure vs. temperature curve are the same with those of BF series low-temperature service valves.)



CNG/NGV Application

BF series ball valves with ECE R110 manual valve type approval available.

Classification: Class 0

Temperature rating: -40°F to 248°F (-40°C to 120°C)

Pressure rating: 3770 psig (260 bar)

CNG/NGV application valves have low-temperature FKM O-rings and PEEK seats. All other materials are the same as those of standard valves.

To order a valve for CNG/NGV application, add **-R110** into the valve ordering number.

For example: BFSS-FL4-P-**R110**

BFSS-FL4-P-3-**R110**

Seal kit for field replacement is available, see "Seal Kits" on Page B-09.

Seal Kits

Valve Series	Flow Pattern	Special Application	Basic Seal Kit Ordering Number	Content
BF	2-way	/	BFSS-2-□	Seat retainer backup ring, seat retainer O-ring, seat retainer guide, end connection seal, trunnion O-ring, trunnion backup ring, ball, seat spring, seat retainer, seat, stem, stem washer, stem O-ring, instructions.
		Low-temperature service	BFSS-2-□-LT	
		CNG/NGV application	BFSS-2-P-R110	
	3-way	/	BFSS-3-□	Seat retainer backup ring, seat retainer O-ring, seat retainer guide, end connection seal, trunnion bearing, ball, seat spring, seat retainer, seat, stem, stem washer, stem O-ring, secondary stem backup ring, primary stem backup ring, instructions.
		Low-temperature service	BFSS-3-□-LT	
		"Fast Fill" CNG filling station application	BFSS-3DL-P	
			BFSS-3DL-P-LT	
		CNG/NGV application	BFSS-3-P-R110	
BFH	2-way	/	BFHSS-2-P	Seat retainer backup ring, seat retainer O-ring, seat retainer guide, end connection seal, ball, seat spring, seat retainer, seat, stem, stem washer, stem O-ring, secondary stem backup ring, primary stem backup ring, instructions.
		Low-temperature service	BFHSS-2-P-LT	
	3-way	/	BFHSS-3-P	
		Low-temperature service	BFHSS-3-P-LT	

Seat Material	Designator
PTFE	T
PCTFE	K
PEEK	P

1. Seal kit components are the same materials and grades listed in materials of construction.

2. To order seal kits for BF series standard and low-temperature service ball valves, select a seat designator from the table at left and add to the basic seal kit ordering number.

Example: BFSS-2-T

BFSS-2-P-LT

3. The listed basic seal kit ordering numbers specify 316 stainless steel material.

To order kits with other materials, such as Alloy 400 material, replace "SS" with "M" in the ordering number.


Example: BFM-2-T

Locking Device

⊙ Lock BF series 2-way or 3-way valves, locking hole diameter is 0.21 in (5.2 mm).

⊙ To order a ball valve with locking device, add **-L** to the valve ordering number.

Example: BFSS-ML6-L/BFSS-ML6-3-L



Ball Valve without Handle

⊙ Ball Valve without handle can be directly connected to the FITOK actuator assembly.

⊙ To order, please add **-AM** to the valve ordering number.

Example: BFSS-FL4-P-AM

Ordering Number Description

Series		Body Material		Connection 1 Type		Connection 1 Size		Connection 2 Type		Connection 2 Size		Seat Material		Handle/Actuator		For Actuator		Flow Pattern		Locking Device		Special Application		Cleaning and Packaging																																																																																																					
BF	SS	316 SS		FNS	Female NPT	2	1/8"	Same as Connection 1	Specified in the same way as connection 1 type and size	BF Series	Black Nylon Handle	None	2-Way	No	None	FC-01																																																																																																													
BFH	M	Alloy 400		NS	Male NPT	4	1/4"										PTFE	I	Red Nylon Handle	H	Mechanical Limit Switch	3	3-Way	L	Yes	S	NACE MR0175	F2	FC-02																																																																																																
				FRT	Female BSPT	6	3/8" or 6 mm																							PCTFE	GR	Green Nylon Handle	N	Inductive Limit Switch	3DL	3-Way "Fast Fill"			SI	Inert Silicon Coating																																																																																					
				RT	Male BSPT	8	1/2" or 8 mm																																				PEEK	J	Blue Nylon Handle	Q	Solenoid Valve					CE	CE Certification																																																																								
				FRP	Female BSPP (for RP)	10	10 mm																																																	BFH Series	AM	Without Handle	HQ	Mechanical Limit Switch and Solenoid Valve					LT	Low-temperature Service																																																											
				BP	Male BSPP (for RG)	12	12 mm																																																														P	PEEK	C	NQ	Inductive Limit Switch and Solenoid Valve					R110	ECE R110																																														
				FMS	Female Metric Thread (for RG-M)																																																																													90° Normally Closed Pneumatic Actuator	O	90° Normally Open Pneumatic Actuator																																									
				MS	Male Metric Thread (for RG-M)																																																																																										D	90° Double Acting Pneumatic Actuator																													
				FL	Fractional Tube Fitting																																																																																																							LX	180° Left End Normally Open Pneumatic Actuator																
				ML	Metric Tube Fitting																																																																																																																				RX	180° Right End Normally Open Pneumatic Actuator			
								DX	180° Double Acting Pneumatic Actuator																																																																																																																				
																	E	90° Electric Actuator																																																																																																											
																														EX	180° Electric Actuator																																																																																														
																				</																																																																																																									

Note: "Ordering Number Description" is a reference to understand the combination rules of FITOK product part number. Not all combinations are available.

1. Cleaning and Packaging:
FC-01: Standard cleaning and packaging for general industrial procedures.
FC-02: Special cleaning and packaging for wetted system components to ensure compliance with product cleanliness requirement of ASTM G93 Level C.
2. For more information about pneumatically actuated ball valves, please refer to the catalog Actuated Ball Valves.
3. Inert Silicon Coating: Except for ball valves with PEEK seat, wetted metal components Inert Silicon coated.
4. CE certification is available. For more information, please contact FITOK group or our authorized distributors.
5. Certifications do not include attachments to the valve, such as actuators or a different handle mechanism.

3-Piece Ball Valves


BG Series

Features

- Working pressures up to 1,000 psig (69 bar)
- Working temperature: -20°F to 450°F (-28°C to 232°C)
- Maximum-flow design with Cv up to 93
- Blowout-proof stem minimizes failures caused by stem movement or looseness
- Floating ball design compensates for seat wear, improving leak-tight integrity
- Each valve is factory leak-tested with nitrogen or compressed air at rated pressure




Pressure vs. Temperature



Note: The temperature and pressure rating are based on valves of standard materials.




Standard Materials of Construction



Item	Component	Valve Body Material	
		CF8M/A351	CF8/A351
1	Stem Nut	SS	
2	Gasket	SS	
3	Handle	304 SS/A240 (with vinyl sleeve)	
4	Gland	316 SS/A479 or 304 SS/A479	
5	Upper Packing	PTFE/D1710	
6	Stem	316 SS/A479 or 304 SS/A479	
7	Lower Bearing	PTFE/D1710	
8	Body	CF8M/A351	CF8/A351
9	Body Bolt	SS	
10	Ball	316 SS/A479 or 304 SS/A479	
11	Support Ring	316 SS/A240 or 304 SS/A240	
12	Flange Seal	PTFE/D1710	
13	Seat	PTFE/D1710	
14	End Connection	CF8M/A351	CF8/A351
15	Gasket	SS	
16	Nut	SS	
Lubricants		Silicone-based and PTFE-based	

Note: Wetted components are listed in italics.
For other materials, please contact FITOK Group or our authorized distributors.

Dimensions



Basic Ordering Number	Connection Type and Size		Orifice in. (mm)	Cv	Dimensions, in. (mm)				
	Connection 1	Connection 2			A	B	W	X	Y
BG□□-FNS2-05	1/8 Female NPT	1/8 Female NPT	0.19 (4.8)	1.2	2.05 (52.1)	1.03 (26.0)	0.63 (16.0)	2.69 (68.3)	1.46 (37.0)
BG□□-FRP2-05	1/8 Female BSPP	1/8 Female BSPP							
BG□□-PB4-05	1/4×SCH80 Pipe Butt Weld	1/4×SCH80 Pipe Butt Weld							
BG□□-FL4-05	1/4" FITOK	1/4" FITOK							
BG□□-ML6-05	6 mm FITOK	6 mm FITOK							
BG□□-ML8-05	8 mm FITOK	8 mm FITOK							
BG□□-FNS4-07	1/4 Female NPT	1/4 Female NPT	0.28 (7.1)	3.8	2.05 (52.1)	1.03 (26.0)			
BG□□-FRP4-07	1/4 Female BSPP	1/4 Female BSPP							
BG□□-FL6-07	3/8" FITOK	3/8" FITOK							
BG□□-ML10-07	10 mm FITOK	10 mm FITOK							
BG□□-FL8-11	1/2" FITOK	1/2" FITOK	0.42 (10.6)	7.5	4.04 (103.0)	2.02 (51.3)			
BG□□-ML12-11	12 mm FITOK	12 mm FITOK							
BG□□-ML14-11	14 mm FITOK	14 mm FITOK							
BG□□-FNS6-13	3/8 Female NPT	3/8 Female NPT	0.50 (12.7)	11.3	2.57 (65.2)	1.28 (32.6)	0.93 (23.5)	3.94 (100.0)	2.19 (55.7)
BG□□-FRP6-13	3/8 Female BSPP	3/8 Female BSPP							
BG□□-PS6-13	3/8 PS	3/8 PS							
BG□□-PB8-13	1/2×SCH80 Pipe Butt Weld	1/2×SCH80 Pipe Butt Weld			2.96 (75.3)	1.48 (37.7)			
BG□□-FL10-13	5/8" FITOK	5/8" FITOK							
BG□□-ML16-13	16 mm FITOK	16 mm FITOK			4.04 (103.0)	2.02 (51.3)			
BG□□-FNS8-15	1/2 Female NPT	1/2 Female NPT	0.55 (14.0)	13.0			2.74 (69.5)	1.37 (34.8)	1.06 (27.0)
BG□□-FRP8-15	1/2 Female BSPP	1/2 Female BSPP							
BG□□-PS8-15	1/2 PS	1/2 PS							
BG□□-MTB22-15	22×3 mm Tube Butt Weld	22×3 mm Tube Butt Weld							
BG□□-TS12-15	3/4" TS	3/4" TS			4.04 (103.0)	2.02 (51.3)			
BG□□-MTS18-15	18 mm Tube Socket Weld	18 mm Tube Socket Weld							
BG□□-FL12-15	3/4" FITOK	3/4" FITOK							
BG□□-ML18-15	18 mm FITOK	18 mm FITOK							
BG□□-FNS12-20	3/4 Female NPT	3/4 Female NPT	0.79 (20.0)	50.0	3.15 (80.0)	1.57 (40.0)	1.34 (34.0)	5.18 (131.5)	2.66 (67.5)
BG□□-FRP12-20	3/4 Female BSPP	3/4 Female BSPP							

Basic Ordering Number	Connection Type and Size		Orifice in. (mm)	Cv	Dimensions, in. (mm)				
	Connection 1	Connection 2			A	B	W	X	Y
BG□□-PB12-20	3/4×SCH80 Pipe Butt Weld	3/4×SCH80 Pipe Butt Weld	0.79 (20.0)	34	3.15 (80.0)	1.57 (40.0)	1.34 (34.0)	5.18 (131.5)	2.66 (67.5)
BG□□-PS12-20	3/4 PS	3/4 PS							
BG□□-TS16-20	1" TS	1" TS							
BG□□-MTB25-20	25×3.5 mm Tube Butt Weld	25×3.5 mm Tube Butt Weld							
BG□□-MTS25-20	25 mm Tube Socket Weld	25 mm Tube Socket Weld			5.12 (130.0)	2.56 (65.0)	1.34 (34.0)	5.18 (131.5)	2.66 (67.5)
BG□□-FL16-20	1" FITOK	1" FITOK							
BG□□-ML22-20	22 mm FITOK	22 mm FITOK							
BG□□-ML25-20	25 mm FITOK	25 mm FITOK							
BG□□-FNS16-25	1 Female NPT	1 Female NPT	0.98 (25.0)	65	3.54 (90.0)	1.77 (45.0)	1.57 (40.0)	5.95 (151.2)	3.08 (78.2)
BG□□-FRP16-25	1 Female BSPP	1 Female BSPP							
BG□□-PS16-25	1 PS	1 PS							
BG□□-PB16-25	1×SCH80 Pipe Butt Weld	1×SCH80 Pipe Butt Weld							

1. FITOK means FITOK double ferrule tube fittings, TS means fractional tube socket weld, MTS means metric tube socket weld, TB means fractional tube butt weld, MTB means metric tube butt weld, PS means pipe socket weld, and PB means pipe butt weld.
2. Butt welding ends are manually welded. For connections with orbital welding, please contact FITOK Group or our authorized distributors.
3. Sizes and types listed are standard. Other sizes and types are available upon request, please contact FITOK Group or our authorized distributors.
4. Dimensions are shown with tube fitting nuts finger-tightened. All dimensions are for reference only and are subject to change. For dimensions not shown above, please contact FITOK Group or our authorized distributors.

Seal Kits

Valve Orifice	Basic Seal Kit Ordering Number	Content
05/07	T-BG-2-RK	Seat, flange seal, lower packing, upper packing, instructions
11/13	T-BG-4-RK	
15	T-BG-6-RK	
20	T-BG-12-RK	
25	T-BG-16-RK	Seat, flange seal, stem bearing, packing support, lower packing, upper packing, instructions

Locking Device

- Lock BG series valves, locking hole diameters of:
valves with orifice 05 or 07 are 0.185 in (4.7 mm);
valves with orifice 11, 13, 15, or 20 are 0.22 in (5.7 mm);
valves with orifice 25 are 0.19 in (4.8 mm)
- To order a ball valve with locking device, add -L to the valve ordering number.
Example: BGSS-FRT8-15-L




Diagram of Ball Valves with Locking Device and Orifice 05, 07, 11, 13, 15, or 20




Diagram of Ball Valves with Locking Device and Orifice 25

Ordering Number Description

BGSS - FNS8 - ML18 - 15 - L - SF2																			
Series		Body Material		Connection 1 Type		Connection 1 Size		Connection 2 Type		Connection 2 Size		Orifice Size		Locking Device		Special Application		Cleaning and Packaging	
BG	SS	CF8M	FNS	Female NPT	2	1/8"	Same as Connection 1	Specified in the same way as connection 1 type and size	05	0.19" (4.8 mm)		L	No	None	S	NACE MR0175	F2	FC-01	
	S4	CF8	NS	Male NPT	4	1/4" or 1/4xSCH80				07 0.28" (7.1 mm)			Yes			S		FC-02	
			FRT	Female BSPT	5	5/16"			11	0.42" (10.6 mm)									
			RT	Male BSPT	6	3/8" or 6 mm			13	0.50" (12.7 mm)									
			FRP	Female BSPP (for RP)	8	1/2" or 8 mm or 1/2xSCH80			15	0.55" (14.0 mm)									
			BP	Male BSPP (for RG)	10	5/8" or 10 mm			20	0.79" (20 mm)									
			FMS	Female Metric Thread (for RG-M)	12	3/4" or 12 mm or 3/4xSCH80			25	0.98" (25 mm)									
			MS	Male Metric Thread (for RG-M)	14	14 mm or M14 x 1.5													
			MTS	Metric Tube Socket	16	1" or 16 mm or 1"xSCH80													
			TS	Fractional Tube Socket	18	18 mm													
			MTB	Metric Tube Butt Weld	20	1 1/4" or 20 mm or M20 x 1.5													
			TB	Fractional Tube Butt Weld	22	22 mm or 22x3 mm or M22x1.5													
			PS	Pipe Socket Weld	24	1 1/2" or M24 x 1.5													
			PB	Pipe Butt Weld	25	25 mm or 25x3.5 mm													
			FL	Fractional Tube Fitting															
			ML	Metric Tube Fitting															
			UFB	Rotatable Fractional Tube Butt Weld															
			UMB	Rotatable Metric Tube Butt Weld															
			UPB	Rotatable Pipe Butt Weld															

Note: "Ordering Number Description" is a reference to understand the combination rules of FITOK product part number. Not all combinations are available.

1. Standard thread pitch for metric threads are as follows:
M10 and below: 1 mm
M12 to M24: 1.5 mm
Standard thread pitch should be omitted in the ordering number, others should be specified.

2. If you need a port with orbital welding, please contact FITOK Group.

3. For oxygen-enriched environment or hazardous media service, contact FITOK Group or our authorized distributors.

4. Cleaning and Packaging:
FC-01: Standard cleaning and packaging for general industrial procedures.
FC-02: Special cleaning and packaging for wetted system components to ensure compliance with product cleaning requirement of ASTM G93 Level C.


5. Inert Silicon Coating: Wetted metal components Inert Silicon coated.

3-Piece Ball Valves

BH Series

Features


- Working pressures up to 3,000 psig (207 bar)
- Working temperature: -20°F to 450°F (-28°C to 232°C)
- Maximum-flow design with Cv up to 130
- Floating ball design paired with disc-spring-loaded seats to compensate for seat wear and pressure/temperature changes, improving leak-tight integrity
- Blowout-proof stem minimizes failures caused by stem movement or looseness
- Available in 2-way or 3-way flow patterns
- Each valve is factory leak-tested with nitrogen or compressed air at rated pressure
- Fire-safe ball valves available
- Low-temperature service option available




Pressure vs. Temperature

2-way Valves


Orifice Size: 0.19", 0.28", 0.41", 0.52" & 0.88"



Orifice Size: 1.13", 1.25" & 1.50"




3-way Valves





Note: The temperature and pressure rating are based on valves of standard materials.

Standard Materials of Construction


2-way Valves



3-way Valves



Port 1 to port 2




Port 1 to port 3

Item	Component	Material Grade/ASME Specification	
1	Body	CF8M/A351	CF8/A351
2	Seat	PTFE or Reinforced PTFE or PEEK	
3	Ball	316 SS/A479	
4	Coned-disc Spring	Strain-hardened 316 SS/A240	
5	Stem Bearing	PEEK	
6	Lower Packing	Reinforced PTFE	
7	Upper Packing	Reinforced PTFE	
8	Body Bolt	Gr. B8M/A193	
9	Stem Spring	Strain-hardened 316 SS/A240	
10	Stem	316 SS/A479	
11	Stem Spring	Strain-hardened 316 SS/A240	
12	Stem Nut	Gr. 8M/A194	
13	Handle Sleeve	Vinyl	
14	Handle	304 SS/A240	
15	Stop Plate	304 SS/A240	
16	Stem Nut	Gr. 8M/A194	
17	Grounding Spring	302 SS/A313	
18	Gland	PTFE-coated 316 SS/A479	
19	Packing Support	PEEK	
20	Flange Seal	PTFE/D1710	
21	Support Ring	316 SS/A240	
22	End Connection	CF8M/A351	CF8/A351
23	Body Nut	Gr.8M/A194	
Lubricants		Silicone-based and PTTE-based	

Note: Wetted components are listed in italics.
For other materials, please contact FITOK Group or our authorized distributors.

Dimensions

2-way Valves



Basic Ordering Number	Connection Type and Size		Orifice in. (mm)	Cv	Dimensions, in. (mm)				
	Connection 1	Connection 2/3			A	B	C	D	E
BHSS-FL4-05	1/4" FITOK	1/4" FITOK	0.19 (4.8)	1.2	3.17 (80.5)	1.59 (40.4)	0.68 (17.3)	1.66 (42.2)	2.37 (60.2)
BHSS-FL4-P05	1/4" FITOK	1/4" FITOK							
BHSS-ML6-05	6 mm FITOK	6 mm FITOK							
BHSS-FNS4-07	1/4 Female NPT	1/4 Female NPT	0.28 (7.1)	3.8	2.16 (54.9)	1.08 (27.4)	0.68 (17.3)	1.66 (42.2)	2.37 (60.2)
BHSS-FNS4-R07	1/4 NPT Female	1/4 NPT Female			3.17 (80.5)	1.59 (40.4)			
BHSS-FL6-07	3/8" FITOK	3/8" FITOK							
BHSS-FL6-R07	3/8" FITOK	3/8" FITOK							
BHSS-FL6-P07	3/8" FITOK	3/8" FITOK							
BHSS-FL8-10	1/2" FITOK	1/2" FITOK	0.41 (10.4)	7.5	4.04 (103)	2.02 (51.3)	0.89 (22.6)	2.35 (59.7)	4.50 (114)
BHSS-FL8-R10	1/2" FITOK	1/2" FITOK							
BHSS-FL8-P10	1/2" FITOK	1/2" FITOK							
BHSS-ML12-10	12 mm FITOK	12 mm FITOK							
BHSS-ML12-R10	12 mm FITOK	12 mm FITOK							
BHSS-ML12-P10	12 mm FITOK	12 mm FITOK							
BHSS-FNS8-13	1/2 Female NPT	1/2 Female NPT	0.52 (13.1)	12.0	2.70 (68.6)	1.35 (34.3)	0.89 (22.6)	2.35 (59.7)	4.50 (114)
BHSS-FNS8-R13	1/2 Female NPT	1/2 Female NPT							
BHSS-FNS8-P13	1/2 NPT Female	1/2 Female NPT							
BHSS-FL12-13	3/4" FITOK	3/4" FITOK		13.6	4.04 (103)	2.02 (51.3)			
BHSS-FL12-R13	3/4" FITOK	3/4" FITOK							
BHSS-FL12-P13	3/4" FITOK	3/4" FITOK							
BHSS-ML16-13	16 mm FITOK	16 mm FITOK							
BHSS-ML18-13	18 mm FITOK	18 mm FITOK		6.8	2.69 (68.3)	1.34 (34)			
BHSS-PB8-13	1/2×SCH80 Pipe Butt Weld	1/2×SCH80 Pipe Butt Weld							

B-20 Ball Valves

Basic Ordering Number	Connection Type and Size		Orifice in.(mm)	Cv	Dimensions, in. (mm)				
	Connection 1	Connection 2/3			A	B	C	D	E
BHSS-FNS12-22	3/4 Female NPT	3/4 Female NPT	0.88 (22.2)	31.0	3.59 (91.2)	1.80 (45.7)	1.25 (31.8)	2.94 (74.7)	6.00 (152)
BHSS-FNS12-R22	3/4 Female NPT	3/4 Female NPT							
BHSS-FNS12-P22	3/4 Female NPT	3/4 Female NPT							
BHSS-FNS16-22	1 Female NPT	1 Female NPT	0.88 (22.2)	38.0	3.59 (91.2)	1.80 (45.7)	1.25 (31.8)	2.94 (74.7)	6.00 (152)
BHSS-FNS16-R22	1 Female NPT	1 Female NPT							
BHSS-FNS16-P22	1 Female NPT	1 Female NPT							
BHSS-FL16-22	1" FITOK	1" FITOK		40.0	5.36 (136)	2.68 (68)			
BHSS-FL16-R22	1" FITOK	1" FITOK							
BHSS-FL16-P22	1" FITOK	1" FITOK							
BHSS-ML25-22	25 mm FITOK	25 mm FITOK							
BHSS-PS16-22	1" Pipe Socket Weld	1" Pipe Socket Weld		42.0	3.59 (91.2)	1.80 (45.7)			
BHSS-FNS20-32	1 1/4 Female NPT	1 1/4 Female NPT	1.25 (31.8)	90.0	4.39 (112)	2.19 (55.6)	1.53 (38.9)	4.03 (102)	9.14 (232)
BHSS-FNS24-32	1 1/2 Female NPT	1 1/2 Female NPT		100.0					
BHSS-FNS32-38	2 Female NPT	2 Female NPT	1.50 (38.1)	130.0	4.94 (125)	2.47 (62.5)	1.74 (44.2)	4.16 (106)	9.14 (232)

1. FITOK means FITOK double ferrule tube fittings, TS means fractional tube socket weld, MTS means metric tube socket weld, TB means fractional tube butt weld, MTB means metric tube butt weld, PS means pipe socket weld, and PB means pipe butt weld.
2. Sizes and types listed are standard. Other sizes and types are available upon request, please contact FITOK Group or our authorized distributors.
3. Dimensions are shown with tube fitting nuts finger-tightened. All dimensions are for reference only and are subject to change. For dimensions not shown above, please contact FITOK Group or our authorized distributors.

Ball Valves for Special Applications

Fire safe applications

API 607 and ISO 15848-1 certified.

Patented stem packing design and seat design.

Working temperature: -40°F to 400°F (-40°C to 204°C).

Working pressure up to: 1500 psig (103 bar).

Orifice size: 0.19" (4.8 mm) to 1.25" (31.8 mm).

Helium leak rate/stem diameter $\leq 1.78 \times 10^{-6}$ std cm³/s.

To order a fire safe valve, add -IE to the valve ordering number.

For example: BHSS-FL16-22-IE

To order a FDA-compliant fire safe valve, add -FDA-IE to the valve ordering number.

For example: BHSS-FL16-22-FDA-IE



Structure Features

Live-loaded disc spring

Elastic compensation effect

Graphite stem packing

Maintain good sealing performance under fire conditions

PTFE stem packing

Maintain good sealing performance under normal conditions

Metal seal design

Reduce the risk of leakage under fire conditions by reducing the active gap between the spherical surface and the sealing surface

PTFE flange seal

Maintain good sealing performance under normal conditions

PTFE seat

Maintain good sealing performance under normal conditions

Graphite flange seal

Maintain good sealing performance under fire conditions

Anti-static device

Grounding spring to provide anti-static protection


Special bolt construction

Maintain body seal during rapid temperature changes resulting from fire exposure and water quenching

Vented ball

Allow pressure to equalize between the valve body and the upstream port, preventing overpressurization and potential seal blowout under fire conditions

Pressure vs. Temperature



Standard Materials of Construction

Component	Material/ ASME Specification
<i>Disc Spring</i>	<i>Alloy X-750/AMS 5542</i>
Flange Seal	Graphite
Stem Packing	Graphite
<i>Packing Support</i>	<i>316 SS/A479</i>
<i>Stem Lower Bearing</i>	<i>316 SS/A479</i>
<i>Stem Upper Bearing</i>	<i>PEEK</i>
Body Bolt	SS

Notes: Wetted components are listed in italics. Other components not listed are in the same material as components of general service ball valves. For other materials, please contact FITOK Group or our authorized distributors.

Low-Temperature Service

Working Temperature Range: -65°F to 250°F (-54°C to 121°C).

Working Pressure: Up to 3000 psig (207 bar).

Orifice Sizes: 0.19" (4.8 mm) to 0.88" (22.2 mm).

Valves for low-temperature service are equipped with low-temperature EPDM O-rings.

All other materials are the same as those of standard valves.


To order a valve for low-temperature service, add **-LT** to the valve ordering number.

For example: BHSS-FL4-P05-LT

BHSS-FL4-P05-3-LT

Seal kits for field replacement are available (see "Seal Kits" section).

Pressure VS Temperature



Materials of Construction

Component	Material/Specification
Seat	<i>PEEK/Reinforced PTFE</i>
Flange Seal	<i>Low Temperature EPDM</i>
Upper/Lower Packing	<i>Reinforced PTFE</i>

Note: Wetted components are listed in italics. Other components are same as standard materials of construction.

Seal Kits


Valve Orifice	Flow Pattern	Special Application	Basic Seal Kit Ordering Number	Content
05/07	2-way and 3-way	None	BHSS-□4-RK	Seat, disc spring, stem bearing, lower packing, upper packing, stem spring, packing support, flange seal, instructions
		Low-temperature service	BHSS-□4-LT-RK	
10/13		None	BHSS-□8-RK	
		Low-temperature service	BHSS-□8-LT-RK	
22		None	BHSS-□16-RK	
		Low-temperature service	BHSS-□16-LT-RK	
29/32		None	BHSS-□24-RK	
		Low-temperature service	—	
38		None	BHSS-□32-RK	
		Low-temperature service	—	

Seat Material	Designator
PTFE	-
Reinforced PTFE	R
PEEK	P

1. Seal kit components are the same materials and grades listed in materials of construction.
2. The default seat material in the seal kit for BH series valves is PTFE. To order seats with other materials, add a seat material designator to "□" in the basic seal kit ordering number to get a complete ordering number.
Example: BHSS-8-RK
 BHSS-P8-LT-RK
3. The listed basic seal kit ordering numbers specify 316 material.
To order kits with other materials, such as Alloy C-276, replace "SS" with "HC" in the ordering number.
Example: BHHC-8-RK

Locking Device

- ⦿ Lock BH series 2-way or 3-way valves, locking hole diameters of the whole series of valves are 0.20 in (5.0 mm).
- ⦿ To order a ball valve with locking device, add -L to the valve ordering number.
Example: BHSS-FL16-22-L/BHSS-FL16-22-3L



Ball Valve without Handle

- ⦿ Ball Valve without handle can be directly connected to the FITOK actuator assembly.
- ⦿ To order, please add -AM to the valve ordering number.
Example: BHSS-FL4-P05-AM

Ordering Number Description

BHS4 - FNS8 - FRT8 - FL8 - P13G - OHQ3L - SCEF2																																																																																																																																																																																																																																																																																																																																																																																																																														
Series	Body Material	Connection 1 Type	Connection 1 Size	Connection 2/3 Type	Connection 2/3 Size	Seat Material	Orifice Size	Packing Material	Handle/Actuator	For Actuator	Flow Pattern	Locking Device	Special Application	Cleaning and Packaging																																																																																																																																																																																																																																																																																																																																																																																																																
BH	SS	FNS	Female NPT	2	1/8"	Same as Connection 1	05	Reinforced PTFE	I	Yellow Handle Sleeve	None	L	No	None	FC-01																																																																																																																																																																																																																																																																																																																																																																																																															
	CF8M		Male NPT	4	1/4" or 1/4xSCH80											Specified in the same way as Connection 1 type and size	R Reinforced PTFE	07	Graphite	GR	Red Handle Sleeve	H Mechanical Limit Switch	L Yes	S NACE MR0175	F2 FC-02																																																																																																																																																																																																																																																																																																																																																																																																					
S4	CF8	FRT	Female BSPT	5	5/16"	P PEEK	10	0.41" (10.4 mm)	J	Blue Handle Sleeve	N Inductive Limit Switch	Q Solenoid Valve	SI Inert Silicon Coated																																																																																																																																																																																																																																																																																																																																																																																																																	
		FRP	Female BSPP (for RP)	6	3/8" or 6 mm or 3/8xSCH80											22	0.88" (22.2 mm)	EL	Oval Handle with Orange Sleeve	HQ Mechanical Limit Switch and Solenoid Valve	NQ Inductive Limit Switch and Solenoid Valve	CE CE Certification																																																																																																																																																																																																																																																																																																																																																																																																								
		BP	Male BSPP (for RG)	8	1/2" or 8 mm or 1/2xSCH80	29	1.13" (28.6 mm)	AM	Without Handle	C 90°Normally Closed Pneumatic Actuator	O 90°Normally Open Pneumatic Actuator	D 90°Double Acting Pneumatic Actuator	Straight																																																																																																																																																																																																																																																																																																																																																																																																																	
		FMS	Female Metric Thread (for RG)	10	10 mm										32	1.25" (31.8 mm)	C	90°Normally Open Pneumatic Actuator	O	90°Double Acting Pneumatic Actuator	LX 180° Left End Normally Open Pneumatic Actuator	RX 180° Right End Normally Open Pneumatic Actuator	DX 180° Double Acting Pneumatic Actuator																																																																																																																																																																																																																																																																																																																																																																																																							
		MS	Male Metric Thread (for RG)	12	3/4" or 12 mm or 3/4xSCH80	38	1.50" (38.1 mm)	D	90°Double Acting Pneumatic Actuator	LX	RX	DX	E 90° Electric Actuator	EX 180° Electric Actuator																																																																																																																																																																																																																																																																																																																																																																																																																
		MTS	Metric Tube Socket	14	14 mm or M14x1.5										20	1 1/4" or 20 mm or M20x1.5 or 1 1/4xSCH80	22	22 mm or M22x1.5	24	1 1/2" or M24x1.5 or 1-1/2xSCH80	25	25 mm	27	M27x2		28	28 mm	32	2" or 2xSCH80																																																																																																																																																																																																																																																																																																																																																																																																	

1. Standard thread pitch for metric threads are as follows:
M10 and below: 1 mm
M12 to M24: 1.5 mm
M27 and above: 2 mm
Standard thread pitch should be omitted in the ordering number, others should be specified.

2. If you need a port with orbital welding, please contact FITOK Group.

3. FO means FITOK O-ring face seal fittings.

FR means FITOK metal gasket face seal fittings.

4. For oxygen-enriched environment or hazardous media service, contact FITOK Group or our authorized distributors.

5. Cleaning and Packaging:

FC-01: Standard cleaning and packaging for general industrial procedures.

FC-02: Special cleaning and packaging for wetted system components to ensure compliance with product cleanliness requirements of ASTM G93 Level C.

6. For more information about pneumatic actuator ball valves, please refer to the catalog **Actuated Ball Valves**.

7. Inert Silicon Coated: Except for ball valves with PEEK seat, wetted metal components Inert Silicon Coated.

8. CE certification is available. For more information, please contact FITOK group or our authorized distributors

Note: "Ordering Number Description" is a reference to understand the combination rules of FITOK product part number. Not all combinations are available.

One-Piece Instrumentation Ball Valves

BO Series

Features



- ⦿ Working pressures up to 3,000 psig (207 bar)
- ⦿ Working temperature: -65°F to 300°F (-54°C to 148°C)
- ⦿ Cv up to 12
- ⦿ No dead space for enhanced cleanliness
- ⦿ One-piece body and one-piece ball stem for improved sealing performance
- ⦿ Top-loaded design allows adjustment with the valve in-line
- ⦿ Live-loaded design improves thermal cycling performance and compensates for packing wear
- ⦿ Available in 2-way, 3-way, 4-way, 5-way, 6-way or 7-way flow patterns
- ⦿ Angle-pattern flow path available
- ⦿ Each valve is factory leak-tested with nitrogen or compressed air at rated pressure



Notes:

1. To prevent seat leakage, packing adjustment may be required periodically during the service life of the valve.
2. A higher initial actuation torque may happen to the valves that have not been actuated for a period of time.
3. Before installation, instrumentation ball valves exposed to dynamic temperature conditions may lose their initial packing load. Stem packing adjustment should be required.

Standard Materials of Construction



Item	Component	Valve Body Material		
		316 SS	Brass	Alloy 400
		Material Grade/ASTM Specification		
1	Handle	Nylon or Aluminium		
2	Set Screw	Zinc-plated carbon steel		
3	Packing Bolt	316 SS/A479	Brass C36000/B16	316 SS/A479
4	Panel Nut	316 SS/A479	Brass C36000/B16	316 SS/A479
5	Disc Spring	S17700/A693		
6	Gland	316 SS/A479	316 SS/A479	316 SS/A479
7	<i>Packing Seat</i>	<i>PTFE/D1710 or UHMWPE/D4020 or PFA/D3307</i>		
8	<i>Support Ring</i>	316 SS/A479	316 SS/A479	Alloy 400/B164
9	<i>Support Disc</i>			
10	<i>Ball Stem</i>	316 SS/A479	Brass C36000/B16	Alloy 400/B164
11	<i>Body</i>	316 SS/A182	Brass C37700/B283	Alloy 400/B164
<i>Wetted Lubricant</i>		<i>Fluorinated-based and silicone-based</i>		
Non-wetted Lubricant		Molybdenum disulfide with hydrocarbon binder coat		

Note: Wetted components are listed in italics.

For other materials, please contact FITOK Group or our authorized distributors.

On-Off (2-way) Valves

Standard Flow Path

Straight Pattern




Angle Pattern



Pressure vs. Temperature

Straight Pattern and Angle Pattern

PTFE Packing Seat



A1: Straight Pattern Valves (orifice 0.19")


B1: Straight Pattern Valves (orifice 0.05" & 0.06" & 0.09" & 0.13" & 0.28" & 0.41")

Angle Pattern Valves (orifice 0.05" & 0.06" & 0.09" & 0.13" & 0.19")

C1: Angle Pattern Valves (orifice 0.28" & 0.41")

PFA, UHMWPE Packing Seat

The working temperature of UHMWPE packing seat should not be higher than 150°F (65°C).



A2: Straight Pattern Valves (orifice 0.19")


B2: Straight Pattern Valves (orifice 0.05" & 0.06" & 0.09" & 0.13" & 0.28" & 0.41")

Angle Pattern Valves (orifice 0.05" & 0.06" & 0.09" & 0.13" & 0.19")


C2: Angle Valves (orifice 0.28" & 0.41")

Dimensions

Straight Pattern



Angle Pattern



B-28 Ball Valves

Basic Ordering Number	Connection Type and Size	Orifice in. (mm)	Cv		Dimensions, in. (mm)									
			Straight	Angle	A	B	C	D	E ^①	F	G	H		
BO□□-FL1-00	1/16" FITOK	0.05 (1.3)	0.10	—	1.68 (42.7)	0.28 (7.1)	0.34 (8.6)	—	0.25 (6.4)	1.43 (36.2)	1.10 (28)	19/32 (15.1)		
BO□□-FL2-02	1/8" FITOK	0.09 (2.4)	0.20	0.15	2.01 (51.1)			0.97 (24.6)						
BO□□-FL4-03	1/4" FITOK	0.13 (3.2)	0.60	0.35	2.21 (56.1)			1.07 (27.2)						
BO□□-FL4-05		3/8" FITOK	0.19 (4.8)	1.40	0.90	2.39 (60.7)	1.17 (29.7)	0.19 (4.8)	1.64 (41.7)	1.57 (39.9)	25/32 (19.8)			
BO□□-FL6-05	1.50			2.58 (65.5)		1.29 (32.8)								
BO□□-FL6-07			0.28 (7.1)	6.00	2.00	3.05 (77.5)	0.56 (14.2)	0.56 (14.2)	1.43 (36.3)	0.35 (9)	2.19 (55.5)	2.05 (52)	1 1/8 (28.6)	
BO□□-FL8-10	1/2" FITOK	0.41 (10.3)	12.00	4.60	3.92 (99.6)	0.69 (17.5)	0.69 (17.5)	1.74 (44.2)	0.49 (12.5)	2.67 (67.7)	3.13 (79.6)	1 1/2 (38.1)		
BO□□-FL12-10	3/4" FITOK		6.40	3.80										
BO□□-ML3-02	3 mm FITOK	0.09 (2.4)	0.20	0.15	2.01 (51.1)	0.28 (7.1)	0.34 (8.6)	0.97 (24.6)	0.25 (6.4)	1.43 (36.2)	1.10 (28)	19/32 (15.1)		
BO□□-ML6-03	6 mm FITOK	0.13 (3.2)	0.60	0.35	2.21 (56.1)			1.07 (27.2)						
BO□□-ML6-05		0.19 (4.8)	1.40	0.90	2.39 (60.7)			1.17 (29.7)					0.19 (4.8)	1.64 (41.7)
BO□□-ML8-05	8 mm FITOK		1.50		2.46 (62.5)	1.20 (30.5)								
BO□□-ML10-07	10 mm FITOK	0.28 (7.1)	6.00	2.00	3.07 (78.0)	0.56 (14.2)	0.56 (14.2)	1.43 (36.3)	0.35 (9)	2.19 (55.5)	2.05 (52)	1 1/8 (28.6)		
BO□□-ML12-10	12 mm FITOK	0.41 (10.3)	12.00	4.60	3.92 (99.6)	0.69 (17.5)	0.69 (17.5)	1.74 (44.2)	0.49 (12.5)	2.67 (67.7)	3.13 (79.6)	1 1/2 (38.1)		
BO□□-FNS2-03	1/8 Female NPT	0.13 (3.2)	0.50	0.30	1.63 (41.4)	0.28 (7.1)	0.34 (8.6)	0.81 (20.6)	0.25 (6.4)	1.43 (36.2)	1.10 (28)	19/32 (15.1)		
BO□□-FNS2-05		1/4 Female NPT	0.19 (4.8)	1.20	0.70	2.00 (50.8)	0.38 (9.7)	0.44 (11.2)	1.00 (25.4)	0.19 (4.8)	1.64 (41.7)	1.57 (39.9)	25/32 (19.8)	
BO□□-FNS4-05	0.90			0.75	2.06 (52.3)		1.03 (26.2)							
BO□□-FNS4-07			0.28 (7.1)	3.00	1.70	2.50 (63.5)	0.56 (14.2)	0.56 (14.2)	1.25 (31.8)	0.35 (9)	2.19 (55.5)	2.05 (52)	11/8 (28.6)	
BO□□-FNS6-07	3/8 Female NPT	2.60		1.50										
BO□□-FNS8-10	1/2 Female NPT	0.41 (10.3)	6.30	3.50	3.12 (79.2)	0.69 (17.5)	0.69 (17.5)	1.56 (39.6)	0.49 (12.5)	2.67 (67.7)	3.13 (79.6)	11/2 (38.1)		
BO□□-NS4-05	1/4 Male NPT	0.19 (4.8)	1.20	0.75	2.00 (50.8)	0.38 (9.7)	0.44 (11.2)	1.03 (26.2)	0.19 (4.8)	1.64 (41.7)	1.57 (39.9)	25/32 (19.8)		
BO□□-FRT4-05	1/4 Female BSPT		0.90	—	2.06 (52.3)			0.34 (8.6)					0.56 (14.2)	—
BO□□-FRT6-07	3/8 Female BSPT		0.28 (7.1)		2.60									
BO□□-FRT8-10	1/2 Female BSPT	0.41 (10.3)	6.30		3.12 (79.2)	0.69 (17.5)	0.69 (17.5)		0.49 (12.5)	2.67 (67.7)	3.13 (79.6)	1 1/2 (38.1)		
BO□□-FO4-03	1/4 Male FO	0.13 (3.2)	0.60	0.35	1.75 (44.4)	0.38 (9.7)	0.34 (8.6)	0.94 (23.9)	0.25 (6.4)	1.43 (36.2)	1.10 (28)	19/32 (15.1)		
BO□□-FO4-05		0.19 (4.8)	2.40	0.90	1.88 (47.8)		0.44 (11.2)		0.19 (4.8)	1.64 (41.7)	1.57 (39.9)	25/32 (19.8)		
BO□□-FR4-03	1/4 Male FR	0.13 (3.2)	0.60	0.35	2.13 (54.1)			0.34 (8.6)	1.09 (27.7)	0.25 (6.4)	1.43 (36.2)	1.10 (28)	19/32 (15.1)	
BO□□-FR4-05		0.19 (4.8)	2.40	0.90			0.44 (11.2)	0.19 (4.8)		1.64 (41.7)	1.57 (39.9)	25/32 (19.8)		
BO□□-FR8-07	1/2 Male FR	0.28 (7.1)	6.00	—	2.88 (73.2)	0.56 (14.2)	—		0.35 (9)	2.19 (55.5)	2.05 (52)	1 1/8 (28.6)		
BO□□-FR8-10		0.41 (10.3)	12.00			3.12 (79.2)		0.69 (17.5)		0.49 (12.5)	2.67 (67.7)	3.13 (79.6)	1 1/2 (38.1)	

① Min. panel thickness: 3 mm

Switching (3-, 4-, 5-, 6- and 7-Way) Valves


Standard Flow Path

3-way Valves



3L Flow Path

This type of valve can connect one side port to the bottom port or shut off 3 ports. Switch between 0°, 90° and 180° positions with 180° rotation handle.



Ports 1 and 3 open

Off

Ports 1 and 2 open

4-way Valves



4L Flow Path

This type of valve can connect one side port to the bottom port, and shut off other 2 side ports at the same time. Switching can be done in 120° increments with 360° rotation handle.




Ports 1 and 2 open

Ports 1 and 3 open

Ports 1 and 4 open

5-way Valves



5L Flow Path

This type of valve can connect one side port to the bottom port, and shut off other 3 side ports at the same time. Switching can be done in 90° increments with 360° rotation handle.



Ports 1 and 2 open

Ports 1 and 3 open

Ports 1 and 4 open

Ports 1 and 5 open

6-way Valves



6L Flow Path

This type of valve can connect one side port to the bottom port, and shut off other 4 side ports at the same time. Switching can be done in 72° increments with 360° rotation handle.



Ports 1 and 2 open


Ports 1 and 3 open

Ports 1 and 4 open

Ports 1 and 5 open

Ports 1 and 6 open

7-way Valves



7L Flow Path

This type of valve can connect one side port to the bottom port, and shut off other 5 side ports at the same time. Switching can be done in 60° increments with 360° rotation handle.



Ports 1 and 2 open

Ports 1 and 3 open

Ports 1 and 4 open

Ports 1 and 5 open


Ports 1 and 6 open

Ports 1 and 7 open

Pressure vs. Temperature


Switching Valves

PTFE Packing Seat




PFA, UHMWPE Packing Seat

The working temperature of UHMWPE packing seat should not be higher than 150°F (65°C).




Dimensions


3-way Valves



4-and 5-way Valves



6-and 7-way Valves



Basic Ordering Number	Connection Type and Size	Orifice in. (mm)	Cv	Dimensions, in. (mm)							
				A	B	C	D ^①	E	F	H	
	3-way Valves										
BO□□-FL1-00-3L	1/16" FITOK	0.05 (1.3)	0.08	1.68 (42.7)	0.81 (20.6)	0.34 (8.6)	0.25 (6.4)	1.43 (36.2)	1.10 (28)	19/32 (15.1)	
BO□□-FL2-02-3L	1/8" FITOK	0.09 (2.4)	0.15	2.01 (51.1)	0.97 (24.6)						
BO□□-FL4-03-3L	1/4" FITOK	0.13 (3.2)	0.35	2.21 (56.1)	1.07 (27.2)						
BO□□-FL4-05-3L		0.19 (4.8)	0.90	2.39 (60.7)	1.17 (29.7)	0.44 (11.2)	0.19 (4.8)	1.64 (41.7)	1.57 (39.9)	25/32 (19.8)	
BO□□-FL6-07-3L	3/8" FITOK	0.28 (7.1)	2.00	2.89 (73.4)	1.43 (36.3)	0.56 (14.2)	0.35 (9)	2.19 (55.5)	2.05 (52)	11/8 (28.6)	
BO□□-FL8-10-3L	1/2" FITOK	0.41 (10.3)	4.60	3.48 (88.4)	1.74 (44.2)	0.69 (17.5)	0.49 (12.5)	2.67 (67.7)	3.13 (79.6)	11/2 (38.1)	
BO□□-FL12-10-3L	3/4" FITOK		4.90								
BO□□-ML3-02-3L	3 mm FITOK	0.09 (2.4)	0.15	2.01 (51.1)	0.97 (24.6)	0.34 (8.6)	0.25 (6.4)	1.43 (36.2)	1.10 (28)	19/32 (15.1)	
BO□□-ML6-03-3L	6 mm FITOK	0.13 (3.2)	0.35	2.21 (56.1)	1.07 (27.2)						
BO□□-ML6-05-3L		0.19 (4.8)	0.90	2.39 (60.7)	1.17 (29.7)						0.44 (11.2)
BO□□-ML8-05-3L	8 mm FITOK		0.80	2.46 (62.5)	1.20 (30.5)						
BO□□-ML10-07-3L	10 mm FITOK	0.28 (7.1)	2.00	2.89 (73.4)	1.43 (36.3)	0.56 (14.2)	0.35 (9)	2.19 (55.5)	2.05 (52)	1 1/8 (28.6)	
BO□□-ML12-10-3L	12 mm FITOK	0.41 (10.3)	4.60	3.48 (88.4)	1.74 (44.2)	0.69 (17.5)	0.49 (12.5)	2.67 (67.7)	3.13 (79.6)	1 1/2 (38.1)	
BO□□-FNS2-03-3L	1/8 Female NPT	0.13 (3.2)	0.30	1.63 (41.4)	0.81 (20.6)	0.34 (8.6)	0.25 (6.4)	1.43 (36.2)	1.10 (28)	19/32 (15.1)	
BO□□-FNS4-05-3L	1/4 Female NPT	0.19 (4.8)	0.75	2.06 (52.3)	1.03 (26.2)	0.44 (11.2)	0.19 (4.8)	1.64 (41.7)	1.57 (39.9)	25/32 (19.8)	
BO□□-FNS4-07-3L		0.28 (7.1)	1.70	2.5 (63.5)	1.18 (30)	0.56 (14.2)	0.35 (9)	2.19 (55.5)	2.05 (52)	1 1/8 (28.6)	
BO□□-FNS6-07-3L		3/8 Female NPT	1.50								
BO□□-FNS8-10-3L	1/2 Female NPT	0.41 (10.3)	3.50	3.13 (79.5)	1.56 (39.6)	0.69 (17.5)	0.49 (12.5)	2.67 (67.7)	3.13 (79.6)	1 1/2 (38.1)	
BO□□-FRT4-05-3L	1/4 Female BSPT	0.19 (4.8)	0.75	2.06 (52.3)	1.03 (26.2)	0.44 (11.2)	0.19 (4.8)	1.64 (41.7)	1.57 (39.9)	25/32 (19.8)	
BO□□-FRT6-07-3L	3/8 Female BSPT	0.28 (7.1)	1.50	2.5 (63.5)	1.18 (30)	0.56 (14.2)	0.35 (9)	2.19 (55.5)	2.05 (52)	1 1/8 (28.6)	
BO□□-FRT8-10-3L	1/2 Female BSPT	0.41 (10.3)	3.50	3.13 (79.5)	1.56 (39.6)	0.69 (17.5)	0.49 (12.5)	2.67 (67.7)	3.13 (79.6)	1 1/2 (38.1)	
4 - & 5-way Valves											
BO□□-FL2-01-4L	1/8" Female FITOK Tube Fitting	0.06 (1.6)	0.07	2.36 (60)	1.32 (33.5)	0.44 (11.2)	0.20 (5.2)	1.76 (44.6)	1.57 (39.9)	29/32 (23.1)	
BO□□-FL2-01-5L											
BO□□-FNS2-01-4L	1/8 Female NPT	0.06 (1.6)	0.07	1.85 (47)	0.88 (22.4)						
BO□□-FNS2-01-5L				1.55 (39.4)							
BO□□-FNS8-10-4L	1/2 Female NPT	0.41 (10.3)	3.50	3.13 (79.5)	1.56 (39.6)	0.69 (17.5)	0.41 (10.5)	2.67 (70.2)	2.63 (66.7)	1 1/2 (38.1)	
BO□□-FNS8-10-5L											
6 - & 7-way Valves											
BO□□-FL1-00-6L	1/16" Female FITOK Tube Fitting	0.05 (1.3)	0.05	2.64 (67)	1.32 (33.5)	0.44 (11.2)	0.28 (7)	1.76 (44.6)	1.57 (39.9)	29/32 (23.1)	
BO□□-FL1-00-7L											
BO□□-FL2-01-6L	1/8" Female FITOK Tube Fitting	0.06 (1.6)	0.07	2.26 (57.6)	0.97 (24.7)						
BO□□-FL2-01-7L											

① Min. panel thickness: 3 mm

Crossover (4-, 6-Way) Valves

Standard Flow Path

4-way Valves




6-way Valves



4C Flow Path

This type of valve can connect two groups of adjacent ports at the same time. Switch between 0° and 90° positions with 90° rotation handle.



6C Flow Path


This type of valve can connect three groups of adjacent ports at the same time. Switch between 0° and 60° positions with 60° rotation handle.



Pressure vs. Temperature

Crossover Valves

PTFE Packing Seat






A5: 4-way (orifice 0.06")

B5: 4-way (orifice 0.28")

C5: 6-way (orifice 0.05" & 0.06")

PFA, UHMWPE Packing Seat

The working temperature of UHMWPE packing seat should not be higher than 150°F (65°C).

**Dimensions****4-way Valves****6-way Valves**

Basic Ordering Number	Connection Type and Size	Orifice in. (mm)	Cv	Dimensions, in. (mm)					
				A	B	D	E	F	H
4-way Valve									
BO□□-FL1-00-4C	1/16" Female FITOK Tube Fitting ^①	0.05 (1.3)	0.06	1.95 (49.6)	0.44 (11.2)	0.19 (4.8)	1.64 (41.7)	1.57 (39.9)	25/32 (19.8)
BO□□-FL2-01-4C	1/8" Female FITOK Tube Fitting ^①	0.06 (1.6)	0.08	2.61 (66.3)					
BO□□-FNS2-01-4C	1/8 Female NPT ^①			1.55 (39.4)					
BO□□-FNS8-07-4C	1/2 Female NPT ^②	0.28 (7.1)	1.60	3.13 (79.5)	0.69 (17.5)	0.48 (12.2)	2.67 (67.7)	3.13 (79.6)	1 1/2 (38.1)
6-way Valve									
BO□□-FL1-00-6C	1/16" Female FITOK Tube Fitting	0.05 (1.3)	0.06	1.95 (49.5)	0.44 (11.2)	0.19 (4.8)	1.68 (42.7)	1.53 (38.9)	29/32 (23.1)
BO□□-FL2-01-6C	1/8" Female FITOK Tube Fitting	0.06 (1.6)	0.08	2.59 (65.8)					

Notes: Connection type for ball valves in 4L, 5L, 6L, 7L, 4C, 6C, 4H, 4HL, 4V, 5HL, 5H and 5LV flow path is female FITOK tube fitting, which can not be used directly with standard FT and MT connections. Please contact FITOK Group or authorized distributors for use with standard FT and MT connections.

① There might be an across-connection flow during switching. If it is not acceptable to you, please specify a spherical orifice of 0.049 in. Example: BOSS-FL2-01-4C-049.

② There might be an across-connection flow during switching. If it is not acceptable to you, please specify a spherical orifice of 0.093 in. Example: BOSS-FNS8-07-4C-093.

1. FITOK means FITOK double ferrule tube fittings.

2. Sizes and types listed are standard. Other sizes and types are available upon request, please contact FITOK Group or our authorized distributors.

3. Dimensions are shown with tube fitting nuts finger-tightened. All dimensions are for reference only and are subject to change.

For dimensions not shown above, please contact FITOK Group or our authorized distributors.


Special Flow Path

3-way Valves



3HL Flow Path

This type of valve can connect one side port to the bottom port, or connect two side ports to the bottom port. Switching can be done in 90° increments with 180° rotation handle.



Note: For Temperature VS. Pressure curves and dimensions of 3-way valves, see Switching (3-way) Valves above. For Temperature VS. Pressure curves and dimensions of 4-way valves, see Crossover (4-way) Valves above.

4-way Valves



4H Flow Path

This type of valve can connect two opposite ports. Switch between 0° and 90° positions with 90° rotation handle.



4HL Flow Path

This type of valve can connect three adjacent ports and shut off other ports. Switching can be done in 90° increments with 360° rotation handle.



4V Flow Path

This type of valve can connect two adjacent ports and shut off other ports. Switching can be done in 90° increments with 360° rotation handle.



5-way Valves



5H Flow Path

5HL Flow Path

This type of valve can connect three side ports to the bottom port, and shut off the fourth side port at the same time. Switching can be done in 90° increments with 360° rotation handle.


This type of valve can connect the bottom port to port 2 and port 4, or connect the bottom port to port 3 and port 5. Switch between 0° and 90° positions with 90° rotation handle.



5LV Flow Path

This type of valve can connect two adjacent ports to the bottom port, and shut off other two side ports at the same time. Switching can be done in 90° increments with 360° rotation handle.

Note: For Temperature vs. Pressure curve and dimensions of 5-way valves, see Switching (5-way) Valves above.



Vent Port Options

Vented Valves

The maximum working pressure for vented valves is 500 psig (34.5 bar).

Straight-pattern Valves

A vent hole in the side of the valve body makes the downstream port vent to atmosphere when the valve is closed.

Angle-pattern and 3-way Valves

A vent hole in the side of the valve body makes the bottom port vent to atmosphere when the valve is closed.

Welded Vent Port Connections

A FITOK tube fitting or a tube stub welded to the vent port is available for stainless steel vented valves.

Process Option

Valves with FOG process are available. FOG refers to FC-02 without lubrication.

To order a valve with FOG process, add -FOG suffix to the valve ordering number, for example: BOSS-FL4-05-FOG.

The pressure rating of valves with FOG process: 200 psig (13.8 bar) for orifice 10, 500 psig (34.5 bar) for other orifice.


The starting torque of valves with FOG process is greater than that of the lubricated valves.

Bottom Screw Panel Mounting Options


Mounting Dimensions

The bottom screw panel mounting options are not available on angle-pattern valves, 3-way valves, 6-way valves and 7-way valves.


2-way



4-way



5-way



	Orifice in. (mm)	Dimensions, in. (mm)	
		M	N
2-way	0.05~0.13 (1.3~3.2)	0.63 (15.88)	M2.5 x 0.45 deep 0.24" (6)
	0.19 (4.8)	0.88 (22.23)	M3 x 0.5 deep 0.24" (6)
	0.28 (7.1)	1.25 (31.75)	M5 x 0.8 deep 0.24" (6)
	0.41 (10.3)	1.63 (41.28)	M5 x 0.8 deep 0.24" (6)
4-way	0.05~0.06 (1.3~1.6)	1.25 (31.75)	M5 x 0.8 deep 0.24" (6)
	0.28 (7.1)	2.00 (50.8)	M5 x 0.8 deep 0.24" (6)
5-way	0.05~0.06 (1.3~1.6)	1.25 (31.75)	M5 x 0.8 deep 0.24" (6)
	0.41 (10.3)	2.00 (50.8)	M5 x 0.8 deep 0.24" (6)

Locking Device

- ⦿ Locking Device 1 can lock BO series valves with 90° or 180° rotation handle, locking hole diameter is 0.21 in (5.2 mm);
- ⦿ To order a ball valve with locking device 1, add -LH to the valve ordering number.
Example: BOSS-FL6-07-LH/BOSS-FL6-07-3L-LH
- ⦿ Locking Device 2 can lock BO series valves with 90°, 180°, or 360° rotation handle, locking hole diameter is 0.34 in (8.7 mm);
- ⦿ To order a ball valve with locking device 2, add -LK to the valve ordering number.
Example: BOSS-ML6-05-LK/BOSS-ML6-05-5L-LK

Caution: These handles are designed to prevent unintentional valve operation. They are not tamper resistant and can be removed, even when locked.




Diagram of Locking Device 1




Diagram of Locking Device 2

Ball Valve without Handle

- ⦿ Ball Valve without handle can be directly connected to the FITOK actuator assembly.
- ⦿ To order, please add -AM to the valve ordering number.

Example: BOSS-FL4-05-AM

Ordering Number Description

BOSS - ML6 - FL4 - ML8 - H05 - DXHQ3L - BLH - FL4 - SF2

Series	Body Material	Connection 1 Type	Connection 1 Size	Connection 2 to 7 Type	Connection 2 to 7 Size	Seat Material	Orifice Size	Handle/Actuator	For Actuator	Flow Pattern	Panel Installation	Locking Device	Vent Port	Special Application	Cleaning and Packaging
BO	SS 316 SS	FNS Female NPT	1 1/16"	Same as connection 1	Specified in the same way as connection 1 type and size	00 0.05" (1.3 mm)		Black Nylon Handle		None	Straight		No vent port	None	
	S4 304 SS	NS Male NPT	2 1/8"			01 0.06" (1.6 mm)		I Red Nylon Handle	H Mechanical Limit Switch	A Angle		FL2 1/8" tube fitting		S NACE MR0175	
	S1 321 SS	FRT Female BSPT	3 3 mm			02 0.09" (2.4 mm)		GR Green Nylon Handle	N Inductive Limit Switch	3L 3-way		FL4 1/4" tube fitting		SI Inert Silicon Coating	
	6L 316L SS	RT Male BSPT	4 1/4"			03 0.13" (3.2 mm)		J Blue Nylon Handle	Q Solenoid Valve	3HL 3-way		FL6 3/8" tube fitting			
	B Brass	FMS Female Metric Thread (for RG-M)	6 3/8" or 6 mm			05 0.19" (4.8 mm)		AM Without Handle	HQ Mechanical Limit Switch and Solenoid Valve	4L 4-way		ML3 3 mm tube fitting		CE CE Certification	
	M Alloy 400	MS Male Metric Thread (for RG-M)	8 1/2" or 8 mm			07 0.28" (7.1 mm)		U Black Aluminium Handle	NQ Inductive Limit Switch and Solenoid Valve	4H 4-way		ML6 6 mm tube fitting			
		FRP Female BSPP (for RP)	10 10 mm			10 0.41" (10.3 mm)		C 90° Normally Closed Pneumatic Actuator		4HL 4-way		ML8 8 mm tube fitting			FC-01
		FL Fractional Tube Fitting	12 3/4" or 12 mm					O 90° Normally Open Pneumatic Actuator		5L 5-way		No		F2 FC-02	
		ML Metric Tube Fitting	14 14 mm					D 90° Double Acting Pneumatic Actuator		5HL 5-way		LH Locking Device 1		FOG FC-02 without Lubrication	
		FO Male FO Fitting	16 16 mm							5LV 5-way		LK Locking Device 2			
		FR Male FR Fitting	18 18 mm							6L 6-way		Panel nut			
								LX 180° Left End Normally Open Pneumatic Actuator		6C 6-way		B Bottom screw			
								RX 180° Right End Normally Open Pneumatic Actuator		7L 7-way					
								DX 180° Double Acting Pneumatic Actuator							
								E 90° Electric Actuator							
								EX 180° Electric Actuator							

Note: "Ordering Number Description" is a reference to understand the combination rules of FITOK product part number. Not all combinations are available.

- For oxygen-enriched environment or hazardous media service, contact FITOK Group or our authorized distributors.
- Cleaning and Packaging:
FC-01: Standard cleaning and packaging for general industrial procedures.
FC-02: Special cleaning and packaging for wetted system components to ensure compliance with product cleanliness requirement of ASTM G93 Level C.
- For more information about pneumatic actuator ball valves, please refer to the catalog Actuated Ball Valves.
- Inert Silicon Coating: Wetted metal components Inert Silicon coated.
- CE certification is available. For more information, please contact FITOK group or our authorized distributors.

Bar Stock Ball Valves

BP Series

Features


- Working pressures up to 10,000 psig (690 bar)
- Working temperature: -40°F to 450°F (-40°C to 232°C)
- Cv up to 30
- Floating ball design compensates for seat wear, improving leak-tight integrity
- Blowout-proof stem minimizes failures caused by stem movement or looseness
- Available in 2-way or 3-way flow patterns
- Each valve is factory leak-tested with nitrogen or compressed air at rated pressure




Pressure vs. Temperature

2-way Valves

Orifice code: 10




Orifice code: 13 and 19




3-way Valves

Orifice code: 10



Orifice code: 13 and 19



Notes: 1. Graphs are with 316 SS body. For information of body in other materials, please contact FITOK Group or our authorized distributors.
2. The working pressure of valves is restricted by materials of the valve body and seat, as well as end connections. When choosing a valve for your applications, please refer to the above Temperature vs. Pressure Curves and the pressure rating in the dimension table. The minimum value shall be the pressure rating of the valve.


Pressure Rating@100°F (38°C)

Material	End Connection	Pressure Rating, psig (bar)
316 SS	FNS4, FNS6, FNS8, NS4, NS6, NS8, FI4, MI6	10000 (690)
	ML10	8400 (578)
	FL6, ML8	7500 (516)
	ML12	6800 (470)
	FL8	6700 (462)
	ML14	6200 (427)
	FL10, FNS12, FNS16, NS12, NS16	6000 (414)
	ML16, FI12	5800 (400)
	ML20	5500 (379)
	ML18	5400 (372)
	ML22	4900 (338)
	FL16	4700 (324)
	ML25	4600 (317)


Note: Maximum working pressure of BP Series ball valves is 10,000 psig. The specified pressure rating is restricted by end connections.

Standard Materials of Construction

2-way Valves



3-way Valves



Item	Component	Body Material
		316 SS
1	<i>End Connection</i>	<i>316 SS/A479</i>
2	<i>Ball</i>	<i>316 SS/A479</i>
3	<i>O-ring^①</i>	<i>FKM</i>
4	<i>Body</i>	<i>316 SS/A479</i>
5	<i>Seat</i>	<i>PVDF or PCTFE or PEEK</i>
6	Stop Pin	SS
7	<i>Stem Packing</i>	<i>PTFE/D1710</i>
8	Stem Washer	316 SS/A479
9	Stem Nut ^②	SS
10	Spring Washer	SS
11	<i>Stem</i>	<i>316 SS/A479</i>
12	Stop Block	304 SS/A240
13	Handle	SS with vinyl cover
14	Lower Packing ^③	PEEK

Note: Wetted components are listed in italics.

For other materials, please contact FITOK Group or our authorized distributors.


① Ball valves with orifice designator 10 and PEEK seats include a PEEK flange seal.

② Ball valves with orifice code 13 or 19 have 2 stem nuts.

③ Lower packing material of ball valves with orifice code 19 is PTFE.

Dimensions


2-way Valves




Basic Ordering Number	Connection Type and Size	Orifice in. (mm)	Cv	Dimensions, in. (mm)				
				A	B	X	Y	S
BP□□-ML6-10	6 mm FITOK	0.19(4.8)	1.2	3.54 (90.0)	1.77 (45.0)	4.57 (116.0)	2.12 (53.9)	1.30 (32.0)
BP□□-ML8-10	8 mm FITOK	0.25(6.4)	2.3	3.60 (91.6)	1.80 (45.8)			
BP□□-ML10-10	10 mm FITOK	0.31(7.9)	3.8	3.70 (94.0)	1.85 (47.0)			
BP□□-ML12-10	12 mm FITOK	0.39 (10.0)	7.5	3.94 (100.0)	1.97 (50.0)			
BP□□-ML14-10	14 mm FITOK							
BP□□-FL4-10	1/4" FITOK	0.19(4.8)	1.2	3.56 (90.4)	1.78 (45.2)			
BP□□-FL6-10	3/8" FITOK	0.28(7.1)	3.7	3.72 (94.6)	1.86 (47.3)			
BP□□-FL8-10	1/2" FITOK	0.39 (10.0)	7.5	3.92 (99.6)	1.96 (49.8)			
BP□□-FNS4-10	1/4 Female NPT			3.03 (77.0)	1.52 (38.5)			
BP□□-FNS6-10	3/8 Female NPT			2.80 (71.0)	1.40 (35.5)			
BP□□-FNS8-10	1/2 Female NPT			3.27 (83.0)	1.63 (41.5)			
BP□□-NS4-10	1/4 Male NPT	0.28(7.1)	3.7	3.36 (85.4)	1.68 (42.7)	5.59 (142.0)	2.54 (64.4)	1.50 (38.0)
BP□□-NS6-10	3/8 Male NPT	0.39 (10.0)	7.5					
BP□□-NS8-10	1/2 Male NPT			3.75 (95.2)	1.88 (47.6)			
BP□□-ML16-13	16 mm FITOK	0.50 (12.7)	10.0	4.42 (112.2)	2.21 (56.1)			
BP□□-ML18-13	18 mm FITOK			4.12 (104.6)	2.06 (52.3)			
BP□□-ML20-13	20 mm FITOK			4.43 (112.6)	2.22 (56.3)			
BP□□-ML22-13	22 mm FITOK			4.29 (109.0)	2.15 (54.5)			
BP□□-FL10-13	5/8" FITOK			4.36 (110.6)	2.18 (55.3)			
BP□□-FL12-13	3/4" FITOK			3.54 (90.0)	1.77 (45.0)			
BP□□-FNS8-13	1/2 Female NPT			4.09 (104.0)	2.05 (52.0)			
BP□□-FNS12-13	3/4 Female NPT			4.14 (105.2)	2.07 (52.6)			
BP□□-NS12-13	3/4 Male NPT							
BP□□-ML20-19	20 mm FITOK	0.71 (18.0)	30.0	4.87 (123.8)	2.43 (61.9)	6.46 (164.0)	2.72 (69.0)	1.96 (50.0)
BP□□-ML22-19	22 mm FITOK			5.11 (129.8)	2.66 (64.9)			
BP□□-ML25-19	25 mm FITOK			4.59 (116.6)	2.29 (58.3)			
BP□□-FL12-19	3/4" FITOK			5.11 (129.8)	2.66 (64.9)			
BP□□-FL16-19	1" FITOK			3.81 (96.8)	1.91 (48.4)			
BP□□-FNS12-19	3/4 Female NPT			4.26 (108.2)	2.13 (54.1)			
BP□□-FNS16-19	1 Female NPT			4.91 (124.8)	2.45 (62.4)			
BP□□-NS16-19	1 Male NPT							

3-way Valves

Vertical Pattern



Port 1 as inlet
180° rotation handle




Port 1 to port 2




Port 1 to port 3


Horizontal Pattern



Port 1 as inlet
90° rotation handle



Port 1 to port 2



Port 1 to port 3

Note: Restricted flow path for BP series: only port 1 as inlet, port 2 and port 3 as outlet

Basic Ordering Number	Connection Type and Size	Orifice in. (mm)	Dimensions, in. (mm)					
	Connection 1/2/3		A	B	C	X	Y	S
BP□□-ML6-10-3□	6 mm FITOK	0.19 (4.8)	3.54 (90.0)	1.77 (45.0)	2.00 (51.0)	4.57 (116.0)	2.12 (53.9)	1.30 (32.0)
BP□□-ML8-10-3□	8 mm FITOK	0.25 (6.4)	3.60 (91.6)	1.80 (45.8)	2.02 (51.3)			
BP□□-ML10-10-3□	10 mm FITOK	0.31 (7.9)	3.70 (94.0)	1.85 (47.0)	2.07 (52.5)			
BP□□-ML12-10-3□	12 mm FITOK	0.39 (10.0)	3.94 (100.0)	1.97 (50.0)	2.18 (55.5)			
BP□□-ML14-10-3□	14 mm FITOK							
BP□□-FL4-10-3□	1/4" FITOK	0.19 (4.8)	3.56 (90.4)	1.78 (45.2)	1.95 (49.5)			
BP□□-FL6-10-3□	3/8" FITOK	0.28 (7.1)	3.72 (94.6)	1.86 (47.3)	2.16 (54.8)			
BP□□-FL8-10-3□	1/2" FITOK	0.39 (10.0)	3.92 (99.6)	1.96 (49.8)	2.13 (54.0)			
BP□□-FNS4-10-3□	1/4 Female NPT		3.03 (77.0)	1.52 (38.5)	1.44 (36.5)			
BP□□-FNS6-10-3□	3/8 Female NPT		2.80 (71.0)	1.40 (35.5)	1.57 (40.0)			
BP□□-FNS8-10-3□	1/2 Female NPT		3.27 (83.0)	1.63 (41.5)	1.83 (46.4)			
BP□□-NS4-10-3□	1/4 Male NPT	0.28 (7.1)	3.36 (85.4)	1.68 (42.7)	1.90 (48.2)			
BP□□-NS6-10-3□	3/8 Male NPT	0.39 (10.0)						
BP□□-NS8-10-3□	1/2 Male NPT		3.75 (95.2)	1.88 (47.6)	2.09 (53.1)			

Basic Ordering Number	Connection Type and Size	Orifice in. (mm)	Dimensions, in. (mm)					
	Connection 1/2/3		A	B	C	X	Y	S
BP□□-ML16-13-3□	16 mm FITOK	0.50 (12.7)	4.42 (112.2)	2.21 (56.1)	2.60 (66.1)	5.59 (142.0)	2.54 (64.4)	1.50 (38.0)
BP□□-ML18-13-3□	18 mm FITOK		4.12 (104.6)	2.06 (52.3)	2.45 (62.3)			
BP□□-ML20-13-3□	20 mm FITOK		4.43 (112.6)	2.22 (56.3)	2.61 (66.3)			
BP□□-ML22-13-3□	22 mm FITOK		4.29 (109.0)	2.15 (54.5)	2.54 (64.5)			
BP□□-FL10-13-3□	5/8" FITOK		4.36 (110.6)	2.18 (55.3)	2.57 (65.3)			
BP□□-FL12-13-3□	3/4" FITOK		3.54 (90.0)	1.77 (45.0)	2.02 (51.2)			
BP□□-FNS8-13-3□	1/2 Female NPT		4.09 (104.0)	2.05 (52.0)	2.44 (62.0)			
BP□□-FNS12-13-3□	3/4 Female NPT		4.14 (105.2)	2.07 (52.6)	2.46 (62.6)			
BP□□-NS12-13-3□	3/4 Male NPT							
BP□□-ML20-19-3□	20 mm FITOK	0.71 (18.0)	4.87 (123.8)	2.43 (61.9)	2.89 (73.4)	6.46 (164.0)	2.72 (69.0)	1.96 (50.0)
BP□□-ML22-19-3□	22 mm FITOK		5.11 (129.8)	2.66 (64.9)	3.00 (76.2)			
BP□□-ML25-19-3□	25 mm FITOK		4.86 (123.4)	2.43 (61.7)	3.02 (76.7)			
BP□□-FL12-19-3□	3/4" FITOK		5.11 (129.8)	2.66 (64.9)	2.85 (72.4)			
BP□□-FL16-19-3□	1" FITOK		3.82 (97.0)	1.91 (48.5)	2.22 (56.5)			
BP□□-FNS12-19-3□	3/4 Female NPT		4.26 (108.2)	2.13 (54.1)	2.72 (69.1)			
BP□□-FNS16-19-3□	1 Female NPT		4.54 (115.2)	2.27 (57.6)	2.72 (69.1)			
BP□□-NS12-19-3□	3/4 Male NPT		4.91 (124.8)	2.45 (62.4)	2.90 (73.9)			
BP□□-NS16-19-3□	1 Male NPT							

1. FITOK means FITOK double ferrule tube fittings.

2. Sizes and types listed are standard. Other sizes and types are available upon request, please contact FITOK Group or our authorized distributors.



3. Dimensions are shown with tube fitting nuts finger-tightened. All dimensions are for reference only and are subject to change.

For dimensions not shown above, please contact FITOK Group or our authorized distributors.

Panel Mounting Options

Dimension for Panel Mounting

Orifice in. (mm)	in. (mm)			
	L1	L2	T1	T2
0.39 (10.0)	1.02 (26.0)	1.02 (26.0)	M4×0.7P deep 0.19 (5.0)	1.18 (30.0)
0.50 (12.7)	1.18 (30.0)	1.18 (30.0)	M5×0.8P deep 0.19 (5.0)	1.18 (30.0)
0.71 (18.0)	1.37 (35.0)	1.57 (40.0)	M5×0.8P deep 0.19 (5.0)	1.50 (38.0)



Seal Kits

Valve Orifice	Flow Pattern	Basic Seal Kit Ordering Number	Content
10	2-way	BPSS-□10-RK	Seat, upper packing, lower packing, O-ring, stem, ball, instructions
	3-way (vertical)	BPSS-□10-3-RK	
	3-way (horizontal)	BPSS-□10-3S-RK	
13	2-way	BPSS-□13-RK	
	3-way (vertical)	BPSS-□13-3-RK	
	3-way (horizontal)	BPSS-□13-3S-RK	
19	2-way	BPSS-□19-RK	
	3-way (vertical)	BPSS-□19-3-RK	
	3-way (horizontal)	BPSS-□19-3S-RK	

Seat Material	Designator
PVDF	-
PCTFE	K
PEEK	P

1. Seal kit components are the same materials and grades listed in materials of construction.
2. The default seat material in the seal kit for BP series valves is PVDF. To order seats with other materials, add a seat material designator to "□" in the basic seal kit ordering number to get a complete ordering number.
Example: BPSS-10-RK
BPSS-P10-RK
3. The listed basic seal kit ordering numbers specify 316 stainless steel material. To order kits with other materials, such as 304 stainless steel material, replace "SS" with "S4" in the ordering number.
Example: BPS4-10-RK

Locking Device

- ⦿ Locking Device 1 locks BP series 2-way and 3-way valves with a locking hole diameter of 0.23 in. (6.0 mm).
- ⦿ To order a ball valve with locking device 1, add **-L** to the valve ordering number.
Example: BPSS-FL4-10-L/BPSS-FL4-10-3S-L/BPSS-FL4-10-3-L
- ⦿ Locking Device 2 locks BP series 2-way and horizontal 3-way valves. The locking hole diameter is 0.23 in. (6.0 mm) for orifices 10 and 13, and 0.28 in. (7.2 mm) for orifice 19.
- ⦿ To order a ball valve with locking device 2, add **-LK** to the valve ordering number.
Example: BPSS-FL4-10-LK/BPSS-FL4-10-3S-LK
- ⦿ When both top mounting holes and locking devices are present, only locking device 2 should be selected. When both bottom mounting holes and locking devices are present, either locking device may be selected.
Example: BPSS-FL4-10-MLK/BPSS-FL4-10-MDL/BPSS-FL4-10-MDLK




Diagram of Locking Device 1

Diagram of Locking Device 2

Ball Valve without Handle

- ⦿ Ball Valve without handle can be directly connected to the FITOK actuator assembly.
- ⦿ To order, please add **-AM** to the valve ordering number.
Example: BPSS-FL12-13-AM

Ordering Number Description

BPSS - ML20 - FL12 - FNS8 - P13 - OHQ3MLK - SCEF2

Series		Body Material	Connection 1 Type		Connection 1 Size	Connection 2/3 Type	Connection 2/3 Size	Seat Material	Orifice Size	Handle/Actuator	For Actuator	Flow Pattern	Panel Mounting	Locking Device	Special Application	Cleaning and Packaging																				
BP	SS	316 SS	FNS	Female NPT	4	1/4" or 4 mm	Same as Connection 1	PVDF	10	Max. 0.39" (10.0 mm)	Yellow Handle Sleeve	None	Straight	No	None	FC-01																				
	S4	304 SS	NS	Male NPT	6												Specified in the same way as Connection 1 type and size	K PCTFE	13	0.50" (12.7 mm)	I Red Handle Sleeve	H Mechanical Limit Switch	3	3-Way (Vertical Pattern)	L Locking Device 1	S NACE MR0175	F2 FC-02									
	S1	321 SS	FRT	Female BSPT	8																							P PEEK	19	0.71" (18.0 mm)	J Blue Handle Sleeve	N Inductive Limit Switch	Q Solenoid Valve	3S 3-Way (Horizontal Pattern)	LK Locking Device 2	SI Inert Silicon Coating
			RT	Male BSPT	10																															
		FRP	Female BSPP (for RP)	12	3/4" or 12 mm	C 90° Normally Closed Pneumatic Actuator	O 90° Normally Open Pneumatic Actuator	D 90° Double Acting Pneumatic Actuator	M With Top Panel Mounting Holes	CE CE Certification																										
		FL	Fractional Tube Fitting	14							14 mm or M14 x 1.5	1" or 16 mm	18 mm	20 mm or M20 x 1.5	22 mm or M22 x 1.5	25 mm	28 mm	30 mm	32 mm	25 mm	28 mm	30 mm	32 mm													
		ML	Metric Tube Fitting	16	1" or 16 mm	18 mm	20 mm or M20 x 1.5	22 mm or M22 x 1.5	25 mm	28 mm														30 mm	32 mm	25 mm	28 mm	30 mm	32 mm							
		UFB	Rotatable Fractional Tube Butt Weld	18							18 mm	20 mm or M20 x 1.5	22 mm or M22 x 1.5	25 mm	28 mm	30 mm	32 mm	25 mm	28 mm	30 mm	32 mm															
		UMB	Rotatable Metric Tube Butt Weld	20	20 mm or M20 x 1.5	22 mm or M22 x 1.5	25 mm	28 mm	30 mm	32 mm												25 mm	28 mm	30 mm	32 mm											
		UPB	Nut + Gasket + Pipe Bulged Nipple	22							22 mm or M22 x 1.5	25 mm	28 mm	30 mm	32 mm	25 mm	28 mm	30 mm	32 mm																	
				25	25 mm	28 mm	30 mm	32 mm	25 mm	28 mm										30 mm	32 mm															
				28							28 mm	30 mm	32 mm	25 mm	28 mm	30 mm	32 mm																			
				30	30 mm	32 mm	25 mm	28 mm	30 mm	32 mm																										
				32							32 mm	25 mm	28 mm	30 mm	32 mm																					
					25 mm	28 mm	30 mm	32 mm																												
									28 mm	30 mm	32 mm																									
					30 mm	32 mm																														
							32 mm																													

1. Standard thread pitch for metric threads are as follows:
M10 and below: 1 mm
M12 to M24: 1.5 mm
M27 and above: 2 mm
Standard thread pitch should be omitted in the ordering number, others should be specified.
2. For oxygen-enriched environment or hazardous media service, contact FITOK Group or our authorized distributors.
3. Cleaning and Packaging:
FC-01: Standard cleaning and packaging for general industrial procedures.
FC-02: Special cleaning and packaging for wetted system components to ensure compliance with product cleanliness requirements of ASTM G93 Level C.
4. For more information about pneumatic actuator ball valves, please refer to the catalog Actuated Ball Valves.
5. Inert Silicon Coating: Except for ball valves with PEEK seat, wetted metal components Inert Silicon coated.
6. CE certification is available. For more information, please contact FITOK group or our authorized distributors.
7. The rated working pressure of BP series ball valves for "NACE MRO175" application is lower than that of standard valves. For detailed pressure values, please contact FITOK Group or our authorized distributors.

Note: "Ordering Number Description" is a reference to understand the combination rules of FITOK product part number. Not all combinations are available.

Hex Bar Stock Ball Valves

BR Series


Features

- Working pressures up to 1,000 psig (69 bar)
- Working temperature: -20°F to 450°F (-28°C to 232°C)
- Cv up to 17.35
- Compact design for minimal space requirements
- Floating ball design compensates for seat wear, improving leak-tight integrity
- Blowout-proof stem minimizes failures caused by stem movement or looseness
- Multiple handle types available
- Each valve is factory leak-tested with nitrogen or compressed air at rated pressure




Ball Valves
Plug Valves

Pressure vs. Temperature



Standard Materials of Construction


Bar Stock Body




Handle Options




Lever Handle




Aluminium Handle (-U)




Nylon Handle (-NY)




Butterfly Handle (-T)



Handle with Locking Device (-LB)



K-Shaped Handle (-KS)



Scorpion Handle with Locking Device (-FZLB)


Item	Component	Material/Specification		
1	Body	<i>316 SS/A479</i>	<i>Alloy 400/B164</i>	<i>Brass C36000/B16</i>
2	Front Seat	<i>PTFE/D1710</i>		
3	Ball	<i>316 SS/A479</i>	<i>Alloy 400/B164</i>	<i>316 SS/A479</i>
4	Back Seat	<i>PTFE/D1710</i>		
5	End Connection	<i>316 SS/A479</i>	<i>Alloy 400/B164</i>	<i>Brass C36000/B16</i>
6	Lower Packing	<i>PTFE/D1710</i>		
7	Washer	<i>316 SS/A479</i>		
8	Handle	<i>304 SS/A240</i>		
8a		Aluminium		
8b		Nylon with 304 SS insert		
9	Sleeve	Vinyl ester		
10	Stem Nut	Stainless steel		
11	Gasket	Stainless steel		
12	Coned-disc Spring	<i>S17700/A693</i>		
13	Stop Pin ^①	Stainless steel		
14	Upper Packing	<i>PTFE/D1710</i>		
15	Stem	<i>316 SS/A479</i>	<i>Alloy 400/B164</i>	<i>316 SS/A479</i>
16	Lock Block	<i>304 SS/A240</i>		

Note: Wetted components are listed in italics.

① A handle with a locking device does not include a stop pin.

Dimensions

Bar Stock Body



Basic Ordering Number	Connection Type and Size	Orifice in. (mm)	Cv	Dimensions, in. (mm)				
	Connection 1/2			A	B	W	X	Y
BR□□-ML6-05	6 mm FITOK	0.19 (4.8)	1.25	2.57 (65.2)	1.50 (38.1)	3/4 (19.05)	2.36 (60)	1.18 (30)
BR□□-ML8-05	8 mm FITOK			2.63 (66.8)	1.53 (38.8)			
BR□□-FL4-05	1/4" FITOK			2.57 (65.2)	1.50 (38.1)			
BR□□-FL5-05	5/16" FITOK			2.63 (66.8)	1.53 (38.8)			
BR□□-FNS2-05	1/8 Female NPT			1.85 (47.0)	1.08 (27.4)			
BR□□-FRP2-05	1/8 Female BSPP			2.00 (50.0)	1.14 (29.0)			
BR□□-FRP4-05	1/4 Female BSPP			2.00 (50.0)	1.14 (29.0)			
BR□□-FNS4-05	1/4 Female NPT			1.85 (47.0)	1.08 (27.4)			
BR□□-ML10-07	10 mm FITOK	0.28 (7.1)	2.50	2.87 (72.9)	1.68 (42.7)	7/8 (22.23)		1.26 (32)
BR□□-FL6-07	3/8" FITOK							
BR□□-FRP6-07	3/8 Female BSPP			2.03 (51.6)	1.18 (30.0)			
BR□□-FNS6-07	3/8 Female NPT							
BR□□-ML12-10	12 mm FITOK	0.35 (8.9)	5.30	3.15 (80.0)	1.83 (46.5)	1 1/16 (27.0)	3.15 (80)	1.54 (39)
BR□□-ML14-10	14 mm FITOK			3.24 (82.2)	1.87 (47.5)			
BR□□-FL8-10	1/2" FITOK			3.15 (80.0)	1.83 (46.5)			
BR□□-FL10-10	5/8" FITOK			3.24 (82.2)	1.87 (47.5)			
BR□□-FRP8-10	1/2 Female BSPP			2.08 (53.0)	1.12 (28.5)	15/16 (24.0)		
BR□□-FNS8-10	1/2 Female NPT			2.08 (53.0)	1.12 (28.5)			
BR□□-ML16-13	16 mm FITOK	0.47 (12.0)	8.60	3.50 (88.9)	2.00 (50.8)	1 1/4 (31.75)	3.94 (100)	2.03 (51.7)
BR□□-ML18-13	18 mm FITOK							
BR□□-FL12-13	3/4" FITOK			2.48 (63.0)	1.30 (33.0)			
BR□□-FRP12-13	3/4 Female BSPP			2.39 (60.7)	1.20 (30.5)			
BR□□-FNS12-13	3/4 Female NPT							
BR□□-ML22-16	22 mm FITOK	0.63 (16.0)	17.35	3.96 (100.6)	2.24 (56.8)	1 1/2 (38.1)		2.15 (54.8)
BR□□-ML25-16	25 mm FITOK			4.31 (109.5)	2.42 (61.5)			
BR□□-FL16-16	1" FITOK			3.25 (82.6)	1.63 (41.3)			
BR□□-FRP16-16	1 Female BSPP							
BR□□-FNS16-16	1 Female NPT			3.00 (76.5)	1.50 (38.1)			


1. FITOK means FITOK double ferrule tube fittings.

2. Sizes and types listed are standard. Other sizes and types are available upon request, please contact FITOK Group or our authorized distributors.


3. Dimensions are shown with FITOK tube fitting nuts finger-tightened. All dimensions are for reference only and are subject to change. For dimensions not shown above, please contact FITOK Group or our authorized distributors.

Locking Device

Body Material	Orifice	Locking Hole Diameter in. (mm)	Example
A variety of optional materials (bar stock)	05	0.19 (4.8)	BRSS-ML12-10-LB BRSS-ML12-10-FZLB
	07		
	10	0.24 (6.2)	
	13		
	16		



BRSS-ML12-10-LB



BRSS-ML12-10-FZLB

Note: Locking device applies only to lever and scorpion handles. For other handle types requiring a locking device, please contact FITOK Group or our authorized distributors.

Seal Kits

Valve Orifice	Basic Seal Kit Ordering Number	Content
05	BRSS-05-RK	Front seat, back seat, ball, lower packing, upper packing, instructions
07	BRSS-07-RK	
10	BRSS-10-RK	
13	BRSS-13-RK	
16	BRSS-16-RK	

1. Seal kit components are the same materials and grades listed in materials of construction.
2. The listed basic seal kit ordering numbers specify 316 stainless steel material. To order kits with other materials, such as 304 stainless steel material, replace "SS" with "S4" in the ordering number.
Example: BRS4-05-RK

Ordering Number Description

BRSS - ML8 - FL4 - 05 - JLB - SF2

Series	Body Material	Connection 1 Type	Connection 1 Size	Connection 2 Type	Connection 2 Size	Orifice	Handle	Locking Device	Special Application	Cleaning and Packaging
BR	SS 316 SS or CF8M	FNS Female NPT	2 1/8"	Same as connection 1		05 0.19" (4.8 mm)	Lever Handle with Yellow Handle Sleeve	No	None	FC-01
	6L 316L SS	NS Male NPT	4 1/4"	Specified in the same way as connection 1 type and size		07 0.28" (7.1 mm)	Lever Handle with Red Handle Sleeve	LB Locking Device	S NACE MR0175	F2 FC-02
	S4 304 SS	FRT Female BSPT	5 5/16"			10 0.35" (8.9 mm)	Lever Handle with Blue Handle Sleeve	Note: Locking device only applies to lever and scorpion handles.	SI Inert Silicon Coating	
	M Alloy 400	RT Male BSPT	6 3/8" or 6 mm			13 0.47" (12.0 mm)	Black Aluminium Handle			
	B Brass	FRP Female BSPP (for RP)	8 1/2" or 8 mm			16 0.63" (16.0 mm)	NY Black Nylon Handle			
		BP Male BSPP (for RG)	10 10 mm				T Butterfly Handle with Yellow Handle Sleeve			
		FL Fractional Tube Fitting	12 3/4" or 12 mm				TI Butterfly Handle with Red Handle Sleeve			
		ML Metric Tube Fitting	14 14 mm or M14 x 1.5				TJ Butterfly Handle with Blue Handle Sleeve			
		UFB Rotatable Fractional Tube Butt Weld	16 1" or 16 mm				FZ Scorpion Handle with Yellow Handle Sleeve			
		UMB Rotatable Metric Tube Butt Weld	18 18 mm				FZI Scorpion Handle with Red Handle Sleeve			
		UPB Nut + Gasket + Pipe Bulged Nipple	20 1 1/4" or 20 mm or M20 x 1.5				FZJ Scorpion Handle with Blue Handle Sleeve			
			22 22 mm or M22 x 1.5				KS K-Shaped Handle			
			25 25 mm							

- Standard thread pitch for metric threads are as follows:
M10 and below: 1 mm
M12 to M24: 1.5 mm
M27 and above: 2 mm
Standard thread pitch should be omitted in the ordering number, others should be specified.
- For oxygen-enriched environment or hazardous media service, contact FITOK Group or our authorized distributors.
- Cleaning and Packaging:
FC-01: Standard cleaning and packaging for general industrial procedures.
FC-02: Special cleaning and packaging for wetted system components to ensure compliance with product cleaning requirement of ASTM G93 Level C.
- Inert Silicon Coating: Wetted metal components Inert Silicon coated.

Note: "Ordering Number Description" is a reference to understand the combination rules of FITOK product part number. Not all combinations are available.

Hex Bar Stock Ball Valves


BRC Series

Features


- Working pressures up to 2,000 psig (138 bar)
- Working temperature: -65°F to 400°F (-54°C to 204°C)
- Cv up to 17.35
- Compact design for minimal space requirements
- Floating ball design compensates for seat wear, improving leak-tight integrity
- Blowout-proof stem minimizes failures caused by stem movement or looseness
- Multiple handle types available
- O-ring stem packing ball valves available, requiring no packing adjustment
- Each valve is factory leak-tested with nitrogen or compressed air at rated pressure



Pressure vs. Temperature



Standard Materials of Construction




Item	Component	Material/Specification	
1	Body	316 SS/A479	Alloy 400/B164
2	Seat	PFA	
3	Ball	316 SS/A479	Alloy 400/B164
4	Sealing Gasket	316L SS/A269	Alloy 400/B164
5	End Connection	316 SS/A479	Alloy 400/B164
6	Lower Packing	RPTFE	
7	Washer	316 SS/A479	
8	Handle	304 SS/A240	
8a		Aluminium	
8b		Nylon with 304 SS insert	
9	Sleeve	Vinyl ester	
10	Stem Nut	Stainless steel	
11	Gasket	Stainless steel	
12	Coned-disc Spring	S17700/A693	
13	Stop Pin ^①	Stainless steel	
14	Upper Packing	RPTFE	
15	Stem	316 SS/A479	Alloy 400/B164
16	Lock Block	304 SS/A240	

Note: Wetted components are listed in italics.

① A handle with a locking device does not include a stop pin.

Dimensions



Basic Ordering Number	Connection Type and Size	Orifice in. (mm)	Cv	Dimensions, in. (mm)				
	Connection 1/2			A	B	W	X	Y
BRC□□-ML6-05	6 mm FITOK	0.19 (4.8)	1.25	2.57 (65.2)	1.50 (38.1)	3/4 (19.05)	2.36 (60)	1.18 (30)
BRC□□-ML8-05	8 mm FITOK			2.63 (66.8)	1.53 (38.8)			
BRC□□-FL4-05	1/4" FITOK			2.57 (65.2)	1.50 (38.1)			
BRC□□-FL5-05	5/16" FITOK			2.63 (66.8)	1.53 (38.8)			
BRC□□-FNS2-05	1/8 Female NPT			1.85 (47.0)	1.08 (27.4)			
BRC□□-FRP2-05	1/8 Female BSPP			2.00 (50.0)	1.14 (29.0)			
BRC□□-FRP4-05	1/4 Female BSPP			2.00 (50.0)	1.14 (29.0)			
BRC□□-FNS4-05	1/4 Female NPT			1.85 (47.0)	1.08 (27.4)			
BRC□□-ML10-07	10 mm FITOK	0.28 (7.1)	2.50	2.87 (72.9)	1.68 (42.7)	7/8 (22.23)		1.26 (32)
BRC□□-FL6-07	3/8" FITOK							
BRC□□-FRP6-07	3/8 Female BSPP			2.03 (51.6)	1.18 (30.0)			
BRC□□-FNS6-07	3/8 Female NPT							
BRC□□-ML12-10	12 mm FITOK	0.35 (8.9)	5.30	3.15 (80.0)	1.83 (46.5)	1 1/16 (27.0)	3.15 (80)	1.54 (39)
BRC□□-ML14-10	14 mm FITOK			3.24 (82.2)	1.87 (47.5)			
BRC□□-FL8-10	1/2" FITOK			3.15 (80.0)	1.83 (46.5)			
BRC□□-FL10-10	5/8" FITOK			3.24 (82.2)	1.87 (47.5)			
BRC□□-FRP8-10	1/2 Female BSPP			2.08 (53.0)	1.12 (28.5)	15/16 (24.0)		
BRC□□-FNS8-10	1/2 Female NPT			2.08 (53.0)	1.12 (28.5)			
BRC□□-ML16-13	16 mm FITOK	0.47 (12.0)	8.60	3.50 (88.9)	2.00 (50.8)	1 1/4 (31.75)	3.94 (100)	2.03 (51.7)
BRC□□-ML18-13	18 mm FITOK							
BRC□□-FL12-13	3/4" FITOK			3.13 (79.5)	1.95 (49.5)			
BRC□□-FRP12-13	3/4 Female BSPP			3.13 (79.5)	1.95 (49.5)			
BRC□□-FNS12-13	3/4 Female NPT	0.63 (16.0)	17.35	3.96 (100.6)	2.24 (56.8)	1 1/2 (38.1)		2.15 (54.8)
BRC□□-ML22-16	22 mm FITOK			4.31 (109.5)	2.42 (61.5)			
BRC□□-ML25-16	25 mm FITOK			3.68 (93.4)	2.14 (54.3)			
BRC□□-FL16-16	1" FITOK			3.43 (87.1)	2.01 (51.1)			
BRC□□-FRP16-16	1 Female BSPP							
BRC□□-FNS16-16	1 Female NPT							

1. FITOK means FITOK double ferrule tube fittings.

2. Sizes and types listed are standard. Other sizes and types are available upon request, please contact FITOK Group or our authorized distributors.

3. Dimensions are shown with FITOK tube fitting nuts finger-tightened. All dimensions are for reference only and are subject to change. For dimensions not shown above, please contact FITOK Group or our authorized distributors.

O-Ring Stem Packing Ball Valves

- ☉ Suitable for applications where adjusting the packing during valve operation is inconvenient.

Materials of Construction

Item	Component	Material/Specification
1	<i>O-ring</i>	<i>Fluorocarbon FKM/EPDM/Buna N/FFKM</i>
2	<i>Lower Packing</i>	<i>PEEK</i>
2	Seal	PTFE

Wetted components are listed in italics.

Other components are consistent with standard materials of construction.


Temperature Range

Stem Packing Material	Designator	Temperature Range °F (°C)
<i>Fluorocarbon FKM</i>	<i>VI</i>	<i>5 ~ 400 (-15 ~ 204)</i>
<i>EPDM</i>	<i>E</i>	<i>-40 ~ 250 (-40 ~ 121)</i>
<i>Buna N</i>	<i>B</i>	<i>0 ~ 250 (-17 ~ 121)</i>
<i>FFKM</i>	<i>Z</i>	<i>14 ~ 400 (-10 ~ 204)</i>

Ordering Information


- ☉ To order an O-ring upper seal ball valve, add the suffix VI to the standard part number.

Example: BRCSS-ML12-10VI




Locking Device

Body Material	Orifice	Locking Hole Diameter in. (mm)	Example
A variety of optional materials (bar stock)	05	0.19 (4.8)	BRCSS-ML12-10-LB BRCSS-ML12-10-FZLB
	07		
	10	0.24 (6.2)	
	13		
	16		



BRCSS-ML12-10-LB



BRCSS-ML12-10-FZLB

Note: The locking device is only applicable to lever and scorpion handles. For other handle types requiring a locking device, please contact FITOK Group or our authorized distributors.

Seal Kits

Valve Orifice	Basic Seal Kit Ordering Number	Content
05	BRCSS-05-RK	Seat, sealing gasket, ball, lower packing, upper packing, instructions
07	BRCSS-07-RK	
10	BRCSS-10-RK	
13	BRCSS-13-RK	
16	BRCSS-16-RK	

1. Seal kit components are the same materials and grades listed in materials of construction.
2. The listed basic seal kit ordering numbers specify 316 stainless steel material. To order kits with other materials, such as 304 stainless steel material, replace "SS" with "S4" in the ordering number.
Example: BRCSS4-05-RK

Ball Valves
Plug Valves

Ordering Number Description

BRCSS – ML8 – FL4 – 05B – JLB – SF2

Series	Body Material		Connection 1 Type		Connection 1 Size		Connection 2 Type	Connection 2 Size	Orifice	Seal Material		Handle		Locking Device	Special Application		Cleaning and Packaging		
BRC	SS	316 SS	FNS	Female NPT	2	1/8"	Same as connection 1	Specified in the same way as connection 1 type and size	05	0.19" (4.8 mm)		RPTFE	I Lever Handle with Yellow Handle Sleeve J Lever Handle with Red Handle Sleeve K Lever Handle with Blue Handle Sleeve U Black Aluminium Handle NY Black Nylon Handle T Butterfly Handle with Yellow Handle Sleeve TI Butterfly Handle with Red Handle Sleeve TJ Butterfly Handle with Blue Handle Sleeve FZ Scorpion Handle with Yellow Handle Sleeve FZI Scorpion Handle with Red Handle Sleeve FZJ Scorpion Handle with Blue Handle Sleeve KS K-Shaped Handle		No		None		FC-01
	6L	316L SS	NS	Male NPT	4	1/4"			07	0.28" (7.1 mm)	VI	Fluorocarbon FKM		LB	Locking Device	S	NACE MR0175	F2	FC-02
	S4	304 SS	FRT	Female BSPT	5	5/16"			10	0.35" (8.9 mm)	B	Buna N		Note: Locking device only applies to lever and scorpion handles					
	M	Alloy 400	RT	Male BSPT	6	3/8" or 6 mm			13	0.47" (12.0 mm)	E	EPDM							
			FRP	Female BSPP (for RP)	8	1/2" or 8 mm			16	0.63" (16.0 mm)	Z	FFKM							
			BP	Male BSPP (for RG)	10	10 mm													
			FL	Fractional Tube Fitting	12	3/4" or 12 mm													
			ML	Metric Tube Fitting	14	14 mm or M14 x 1.5													
			UFB	Rotatable Fractional Tube Butt Weld	16	1" or 16 mm													
			UMB	Rotatable Metric Tube Butt Weld	18	18 mm													
			UPB	Nut + Gasket + Pipe Bulged Nipple	20	1 1/4" or 20 mm or M20 x 1.5													
					22	22 mm or M22 x 1.5													
					25	25 mm													

Standard thread pitch for metric threads are as follows:
M10 and below: 1 mm
M12 to M24: 1.5 mm
M27 and above: 2 mm

Standard thread pitch should be omitted in the ordering number, others should be specified.

In oxygen-enriched environment or hazardous media service, contact FITOK Group or authorized distributors.

1. Standard thread pitch for metric threads are as follows:

M10 and below: 1 mm

M12 to M24: 1.5 mm

M27 and above: 2 mm

Standard thread pitch should be omitted in the ordering number, others should be specified.

2. For oxygen-enriched environment or hazardous media service, contact FITOK Group or our authorized distributors.

3. Cleaning and Packaging:

FC-01: Standard cleaning and packaging for general industrial procedures.

FC-02: Special cleaning and packaging for wetted system components to ensure compliance with product cleaning requirement of ASTM G93 Level C.

4. Inert Silicon Coating: Wetted metal components Inert Silicon coated.

Note: "Ordering Number Description" is a reference to understand the combination rules of FITOK product part number. Not all combinations are available.

High Performance Ball Valves

BV Series

Features


- Working pressures up to 6,000 psig (414 bar)
- Working temperature: -65°F to 450°F (-54°C to 232°C)
- Cv up to 6.42
- Available in 2-way or 3-way flow patterns
- Angle-pattern flow path available
- Each valve is factory leak-tested with nitrogen or compressed air at rated pressure




Ball Valves
Plug Valves

Pressure vs. Temperature

316 SS Body



Brass Body




Note: The working pressure of valves is restricted by materials of the valve body and seat, as well as end connections. When choosing a valve for your applications, please refer to the above Temperature vs. Pressure Curves and the pressure rating in the dimension table. The minimum value shall be the pressure rating of the valve.

Pressure Rating@100°F (38°C)

End Connection	Pressure Rating, psig (bar)	
	Brass	316 SS
FL1, FL2, FL4, ML3, ML6, FNS2, FNS4, FNS6, FNS8, FNS12 NS2, NS4, NS6, NS8, NS12 RT2, RT4, RT6, RT8, RT12 FRT2, FRT4, FRT6, FRT8, FRT12 FRP2, FRP4, FRP6, FRP8, FRP12 BP2, BP4, BP6, BP8, BP12	3000 (207)	6000 (414)
ML8	2300 (159)	
FL6	2200 (152)	
FL8	2100 (145)	
ML12	2000 (138)	
ML10, ML14	1900 (131)	
FL12	1800 (124)	5800 (400)
ML16	1700 (117)	
ML20	1600 (110)	5500 (379)
ML18		5400 (372)
ML22	1450 (100)	4900 (338)

Standard Materials of Construction

Straight Valves




Item	Component	Valve Body Material	
		SS	Brass
1	Handle	Nylon or Aluminium	
2	Packing Nut	316 SS/A479	C36000/B16
3	Panel Nut	316 SS/A479	
4	Body	CF8M/A351	C37700/B283
5	End Connection	316 SS/A479	C36000/B16
6	Connection Ring	PTFE	
7	Ball	316 SS/A479	
8	Seat	PTFE or PCTFE or PEEK	
9	Seat Retainer	316 SS/A479	
10	Seat Packing	PTFE	
11	Stem Back-up Ring	PEEK	
12	Stem Washer	316/A479	
13	Stem Packing	PTFE	
14	Stem	316 SS/A479	
15	Set Screw	Zinc-plated carbon steel	
	Lubricants	Fluorinated-based	

Note: Wetted components are listed in italics.

For other materials, please contact FITOK Group or our authorized distributors.

3-way Valves




Item	Component	Valve Body Material	
		SS	Brass
1	Handle	Nylon or Aluminium	
2	Packing Nut	316 SS/A479	C36000/B16
3	Panel Nut	316 SS/A479	
4	Body	CF8M/A351	C37700/B283
5	End Connection	316 SS/A479	C36000/B16
6	Connection Ring	PTFE	
7	Seat Packing	PTFE	
8	Seat	PTFE or PCTFE or PEEK	
9	Ball	316 SS/A479	
10	Seat Retainer	316 SS/A479	
11	Trunnion Bearing	PEEK	
12	Stem Back-up Ring	PEEK	
13	Stem Packing	PEEK	
14	Stem Washer	316 SS/A479	
15	Stem	316 SS/A479	
16	Set Screw	Zinc-plated carbon steel	
	Lubricants	Fluorinated-based	

Note: Wetted components are listed in italics.

For other materials, please contact FITOK Group or our authorized distributors.

Angle Pattern Valves




Item	Component	Valve Body Material	
		SS	Brass
1	Handle	Nylon or Aluminium	
2	Packing Nut	316 SS/A479	C36000/B16
3	Panel Nut	316 SS/A479	
4	Body	CF8M/A351	C37700/B283
5	Connection Ring	PTFE	
6	End Connection	316 SS/A479	C36000/B16
7	Seat	PTFE or PCTFE or PEEK	
8	Seat Packing	PTFE	
9	Seat Retainer	316 SS/A479	
10	Ball	316 SS/A479	
11	Trunnion Bearing	PEEK	
12	Stem Back-up Ring	PEEK	
13	Stem Packing		
14	Stem Washer	316 SS/A479	
15	Stem	316 SS/A479	
16	Set Screw	Zinc-plated carbon Steel	
	Lubricants	Fluorinated-based	

Note: Wetted components are listed in italics.
For other materials, please contact FITOK Group or our authorized distributors.



Dimensions

Straight Valves



FLOTECH® 1/2" NPT FLOWMETER												
Basic Ordering Number	Connection Type and Size	Orifice in. (mm)	Cv	Dimensions, in. (mm)								
	Connection 1/2			A	B	C	D	E	F	G	H	I
BV□□-FL1-01	1/16" FITOK	0.05 (1.3)	0.06	2.60 (66.0)	1.30 (33.0)	0.36 (9.2)	0.33 (8.5)	0.94 (23.9)	0.79 (20.0)	1.97 (50.0)	0.58 (14.7)	0.18 (4.6)
BV□□-FL2-02	1/8" FITOK	0.09 (2.4)	0.21	2.72 (69.0)	1.36 (34.5)							
BV□□-ML3-02	3 mm FITOK			2.74 (69.6)	1.37 (34.8)							
BV□□-FRT2-04	1/8 Female BSPT	0.17 (4.2)	0.93	2.14 (54.4)	1.07 (27.2)							
BV□□-FRP2-04	1/8 Female BSPP			2.36 (60.0)	1.18 (30.0)							
BV□□-FNS2-04	1/8 Female NPT											
BV□□-RT2-04	1/8 Male BSPT											
BV□□-BP2-04	1/8 Male BSPP			2.70 (68.6)	1.35 (34.3)							
BV□□-NS2-04	1/8 Male NPT											
BV□□-RT4-04	1/4 Male BSPT											
BV□□-BP4-04	1/4 Male BSPP											
BV□□-NS4-04	1/4 Male NPT											
BV□□-FL4-05	1/4" FITOK	0.19 (4.7)	1.04	3.48 (88.4)	1.74 (44.2)	0.48 (12.2)	0.48 (12.2)	1.24 (31.5)	0.59 (25.0)	2.64 (67.0)	0.77 (19.6)	0.25 (6.4)
BV□□-ML6-05	6 mm FITOK			3.50 (89.0)	1.75 (44.5)							
BV□□-FL6-06	3/8" FITOK	0.25 (6.4)	2.34	3.60 (91.4)	1.80 (45.7)							
BV□□-ML8-06	8 mm FITOK			3.56 (90.4)	1.78 (45.2)							
BV□□-ML10-06	10 mm FITOK			3.62 (92.0)	1.81 (46.0)							
BV□□-FRT4-06	1/4 Female BSPT			3.02 (76.8)	1.51 (38.4)							
BV□□-FRP4-06	1/4 Female BSPP											
BV□□-FNS4-06	1/4 Female NPT											
BV□□-RT4-06	1/4 Male BSPT			3.24 (82.2)	1.62 (41.1)							
BV□□-BP4-06	1/4 Male BSPP											
BV□□-NS4-06	1/4 Male NPT											
BV□□-RT6-06	3/8 Male BSPT											
BV□□-BP6-06	3/8 Male BSPP											
BV□□-NS6-06	3/8 Male NPT											
BV□□-FL8-10	1/2" FITOK	0.41 (10.3)	6.42	4.68 (118.8)	2.34 (59.4)	0.75 (19.0)	0.71 (18.0)	1.54 (39.0)	1.42 (36.0)	3.78 (96.0)	0.90 (22.9)	0.38 (9.7)
BV□□-FL12-10	3/4" FITOK											
BV□□-ML12-10	12 mm FITOK	0.37 (9.5)	5.57	4.66 (118.4)	2.33 (59.2)							
BV□□-ML14-10	14 mm FITOK											
BV□□-ML16-10	16 mm FITOK											
BV□□-ML18-10	18 mm FITOK											
BV□□-ML20-10	20 mm FITOK											
BV□□-ML22-10	22 mm FITOK											
BV□□-FRT6-10	3/8 Female BSPT											
BV□□-FRP6-10	3/8 Female BSPP	3.90 (99.0)	1.95 (49.5)									
BV□□-FNS6-10	3/8 Female NPT											
BV□□-FRT8-10	1/2 Female BSPT	4.30 (109.2)	2.15 (54.6)									
BV□□-FRP8-10	1/2 Female BSPP	3.97 (101.0)	1.99 (50.5)									
BV□□-FNS8-10	1/2 Female NPT	4.30 (109.2)	2.15 (54.6)									
BV□□-FRT12-10	3/4 Female BSPT											
BV□□-FRP12-10	3/4 Female BSPP	4.50 (114.2)	2.25 (57.1)									
BV□□-FNS12-10	3/4 Female NPT											
BV□□-RT8-10	1/2 Male BSPT	0.41 (10.3)	6.42	4.44 (112.8)	2.22 (56.4)							
BV□□-BP8-10	1/2 Male BSPP											
BV□□-NS8-10	1/2 Male NPT											
BV□□-RT12-10	3/4 Male BSPT											
BV□□-BP12-10	3/4 Male BSPP											
BV□□-NS12-10	3/4 Male NPT											



3-way Valves



Basic Ordering Number	Connection Type and Size	Orifice in. (mm)	Cv	Dimensions, in. (mm)								
	Connection 1/2/3			A	B	C	D	E	F	G	H	I
BV□□-FL1-01-3	1/16" FITOK	0.05 (1.3)	0.06	2.60 (66.0)	1.30 (33.0)	1.35 (34.3)						
BV□□-FL2-02-3	1/8" FITOK	0.09 (2.4)	0.21	2.72 (69.0)	1.36 (34.5)	1.41 (35.8)						
BV□□-ML3-02-3	3 mm FITOK			2.74 (69.6)	1.37 (34.8)	1.42 (36.1)						
BV□□-FRT2-04-3	1/8 Female BSPT	0.12 (3.0)	0.28	2.14 (54.4)	1.07 (27.2)	1.12 (28.5)						
BV□□-FRP2-04-3	1/8 Female BSPP											
BV□□-FNS2-04-3	1/8 Female NPT											
BV□□-RT2-04-3	1/8 Male BSPT						0.33 (8.5)	0.94 (23.9)	0.79 (20.0)	1.97 (50.0)	0.58 (14.7)	0.18 (4.6)
BV□□-BP2-04-3	1/8 Male BSPP			2.36 (60.0)	1.18 (30.0)	1.23 (31.3)						
BV□□-NS2-04-3	1/8 Male NPT											
BV□□-RT4-04-3	1/4 Male BSPT											
BV□□-BP4-04-3	1/4 Male BSPP			2.70 (68.6)	1.35 (34.3)	1.40 (35.6)						
BV□□-NS4-04-3	1/4 Male NPT											
BV□□-FL4-05-3	1/4" FITOK	0.19 (4.7)	0.70	3.48 (88.4)	1.74 (44.2)	1.88 (47.7)						
BV□□-ML6-05-3	6 mm FITOK			3.50 (89.0)	1.75 (44.5)	1.89 (48.0)						
BV□□-FL6-05-3	3/8" FITOK			3.60 (91.4)	1.80 (45.7)	1.94 (49.2)						
BV□□-ML8-05-3	8 mm FITOK			3.56 (90.4)	1.78 (45.2)	1.92 (48.7)						
BV□□-ML10-05-3	10 mm FITOK			3.62 (92.0)	1.81 (46.0)	1.95 (49.5)						
BV□□-FRT4-05-3	1/4 Female BSPT											
BV□□-FRP4-05-3	1/4 Female BSPP			3.02 (76.8)	1.51 (38.4)	1.65 (41.9)	0.48 (12.2)	1.24 (31.5)	0.59 (25.0)	2.64 (67.0)	0.77 (19.6)	0.25 (6.4)
BV□□-FNS4-05-3	1/4 Female NPT											
BV□□-RT4-05-3	1/4 Male BSPT											
Bv□□-BP4-05-3	1/4 Male BSPP											
BV□□-NS4-05-3	1/4 Male NPT											
BV□□-RT6-05-3	3/8 Male BSPT			3.24 (82.2)	1.62 (41.1)	1.76 (44.6)						
BV□□-BP6-05-3	3/8 Male BSPP											
BV□□-NS6-05-3	3/8 Male NPT											

Basic Ordering Number	Connection Type and Size	Orifice in. (mm)	Cv	Dimensions, in. (mm)								
	Connection 1/2/3			A	B	C	D	E	F	G	H	I
BV□□-FL8-10-3	1/2" FITOK	0.37 (9.5)	3.48	4.68 (118.8)	2.34 (59.4)	2.68 (68.1)	0.71 (18.0)	1.54 (39.0)	1.42 (36.0)	3.78 (96.0)	0.90 (22.9)	0.38 (9.7)
BV□□-FL12-10-3	3/4" FITOK			4.66(118.4)	2.33 (59.2)	2.67 (67.9)						
BV□□-ML12-10-3	12 mm FITOK											
BV□□-ML14-10-3	14 mm FITOK											
BV□□-ML16-10-3	16 mm FITOK			4.84 (123.0)	2.42 (61.5)	2.76 (70.2)						
BV□□-ML18-10-3	18 mm FITOK											
BV□□-ML20-10-3	20 mm FITOK											
BV□□-ML22-10-3	22 mm FITOK			3.90 (99.0)	1.95 (49.5)	2.29 (58.2)						
BV□□-FRT6-10-3	3/8 Female BSPT											
BV□□-FRP6-10-3	3/8 Female BSPP											
BV□□-FNS6-10-3	3/8 Female NPT			4.30 (109.2)	2.15 (54.6)	2.49 (63.3)						
BV□□-FRT8-10-3	1/2 Female BSPT											
BV□□-FRP8-10-3	1/2 Female BSPP											
BV□□-FNS8-10-3	1/2 Female NPT			4.30 (109.2)	2.15 (54.6)	2.49 (63.3)						
BV□□-FRT12-10-3	3/4 Female BSPT											
BV□□-FRP12-10-3	3/4 Female BSPP			4.50 (114.2)	2.25 (57.1)	2.59 (65.8)						
BV□□-FNS12-10-3	3/4 Female NPT											
BV□□-RT8-10-3	1/2 Male BSPT			4.44 (112.8)	2.22 (56.4)	2.56 (65.1)						
BV□□-BP8-10-3	1/2 Male BSPP											
BV□□-NS8-10-3	1/2 Male NPT											
BV□□-RT12-10-3	3/4 Male BSPT											
BV□□-BP12-10-3	3/4 Male BSPP											
BV□□-NS12-10-3	3/4 Male NPT											

Angle Pattern Valves



Basic Ordering Number	Connection Type and Size	Pressure Rating of End Connections @ 100°F (38°C), psig (bar)		Orifice in. (mm)	Cv	Dimensions, in. (mm)									
		Connection 1/2	316 SS			Brass	B	C	D	E	F	G	H	I	
BV□□-FL1-01-A	1/16" FITOK	6000 (414)	3000 (207)	0.05 (1.3)	0.06	1.30 (33.0)	1.35 (34.3)	0.33 (8.5)	0.94 (23.9)	0.79 (20.0)	1.97 (50.0)	0.58 (14.7)	0.18 (4.6)		
BV□□-FL2-02-A	1/8" FITOK	6000 (414)	3000 (207)	0.09 (2.4)	0.21	1.36 (34.5)	1.41 (35.8)								
BV□□-ML3-02-A	3 mm FITOK	6000 (414)	3000 (207)			1.37 (34.8)	1.42 (36.1)								
BV□□-FRT2-04-A	1/8 Female BSPT	6000 (414)	3000 (207)	0.12 (3.0)	0.28	1.07 (27.2)	1.12 (28.5)								
BV□□-FRP2-04-A	1/8 Female BSPP	6000 (414)	3000 (207)			1.18 (30.0)	1.23 (31.3)								
BV□□-FNS2-04-A	1/8 Female NPT	6000 (414)	3000 (207)												
BV□□-RT2-04-A	1/8 Male BSPT	6000 (414)	3000 (207)												
BV□□-BP2-04-A	1/8 Male BSPP	6000 (414)	3000 (207)												
BV□□-NS2-04-A	1/8 Male NPT	6000 (414)	3000 (207)			1.35 (34.3)	1.40 (35.6)								
BV□□-RT4-04-A	1/4 Male BSPT	6000 (414)	3000 (207)												
BV□□-BP4-04-A	1/4 Male BSPP	6000 (414)	3000 (207)												
BV□□-NS4-04-A	1/4 Male NPT	6000 (414)	3000 (207)			0.19 (4.7)	0.70							1.74 (44.2)	1.88 (47.7)
BV□□-FL4-05-A	1/4" FITOK	6000 (414)	3000 (207)					1.75 (44.5)	1.89 (48.0)						
BV□□-ML6-05-A	6 mm FITOK	6000 (414)	3000 (207)	1.80 (45.7)	1.94 (49.2)										
BV□□-FL6-05-A	3/8" FITOK	6000 (414)	2200 (152)	1.78 (45.2)	1.92 (48.7)										
BV□□-ML8-05-A	8 mm FITOK	6000 (414)	2300 (159)	1.81 (46.0)	1.95 (49.5)										
BV□□-ML10-05-A	10 mm FITOK	6000 (414)	1900 (131)	1.51 (38.4)	1.65 (41.9)										
BV□□-FRT4-05-A	1/4 Female BSPT	6000 (414)	3000 (207)												
BV□□-FRP4-05-A	1/4 Female BSPP	6000 (414)	3000 (207)												
BV□□-FNS4-05-A	1/4 Female NPT	6000 (414)	3000 (207)												
BV□□-RT4-05-A	1/4 Male BSPT	6000 (414)	3000 (207)												
Bv□□-BP4-05-A	1/4 Male BSPP	6000 (414)	3000 (207)												
BV□□-NS4-05-A	1/4 Male NPT	6000 (414)	3000 (207)												
BV□□-RT6-05-A	3/8 Male BSPT	6000 (414)	3000 (207)			1.62 (41.1)	1.76 (44.6)								
BV□□-BP6-05-A	3/8 Male BSPP	6000 (414)	3000 (207)												
BV□□-NS6-05-A	3/8 Male NPT	6000 (414)	3000 (207)												

Basic Ordering Number	Connection Type and Size	Orifice in. (mm)	Cv	Dimensions, in. (mm)							
	Connection 1/2			B	C	D	E	F	G	H	I
BV□□-FL8-10-A	1/2 " FITOK	0.37 (9.5)	3.48	2.34(59.4)	2.68(68.1)	0.71 (18.0)	1.54 (39.0)	1.42 (36.0)	3.78 (96.0)	0.90 (22.9)	0.38 (9.7)
BV□□-FL12-10-A	3/4" FITOK			2.33 (59.2)	2.67 (67.9)						
BV□□-ML12-10-A	12 mm FITOK										
BV□□-ML14-10-A	14 mm FITOK										
BV□□-ML16-10-A	16 mm FITOK										
BV□□-ML18-10-A	18 mm FITOK										
BV□□-ML20-10-A	20 mm FITOK			2.42 (61.5)	2.76 (70.2)						
BV□□-ML22-10-A	22 mm FITOK										
BV□□-FRT6-10-A	3/8 Female BSPT			1.95 (49.5)	2.29 (58.2)						
BV□□-FRP6-10-A	3/8 Female BSPP										
BV□□-FNS6-10-A	3/8 Female NPT			2.15 (54.6)	2.49 (63.3)						
BV□□-FRT8-10-A	1/2 Female BSPT										
BV□□-FRP8-10-A	1/2 Female BSPP			1.99 (50.5)	2.33 (59.1)						
BV□□-FNS8-10-A	1/2 Female NPT										
BV□□-FRT12-10-A	3/4 Female BSPT			2.25 (57.1)	2.59 (65.8)						
BV□□-FRP12-10-A	3/4 Female BSPP										
BV□□-FNS12-10-A	3/4 Female NPT			2.22 (56.4)	2.56 (65.1)						
BV□□-RT8-10-A	1/2 Male BSPT										
BV□□-BP8-10-A	1/2 Male BSPP										
BV□□-NS8-10-A	1/2 Male NPT										
BV□□-RT12-10-A	3/4 Male BSPT										
BV□□-BP12-10-A	3/4 Male BSPP										
BV□□-NS12-10-A	3/4 Male NPT										

1. FITOK means FITOK double ferrule tube fittings.

2. Sizes and types listed are standard. Other sizes and types are available upon request, please contact FITOK Group or our authorized distributors.

3. Dimensions are shown with tube fitting nuts finger-tightened. All dimensions are for reference only and are subject to change.

For dimensions not shown above, please contact FITOK Group or our authorized distributors.

Locking Device

Locking Device 1

- Locks BV series 2-way or 3-way valves, featuring a locking hole diameter of 0.21 in (5.2 mm).
- To order a ball valve with Locking Device 1, add - L to the valve ordering number.
Example: BVSS-ML12-10- L/BVSS-ML12-10-3- L

Locking Device 2

- Locks BV series 2-way or 3-way valves, featuring different locking hole diameters:
0.21 in (5.2 mm) for valves with orifice designators 05 and 06
0.34 in (8.7 mm) for valves with orifice designator 10
- To order a ball valve with Locking Device 2, add - LP to the valve ordering number.
Example: BVSS-ML12-10-LP/BVSS-ML12-10-3-LP
- No impact on panel mounting.
- Locking device kits are also available for individual purchase to add locking functionality to your existing standard manual ball valves, with ordering information as follows:

Locking Device 2 Kits

Name	Valve Orifice	Locking Hole Diameter	Kit Ordering Number	Content
Locking Device Kits	05, 06	0.21 in (5.2 mm)	BVS4-06-LP-RK	Upper lock plate, lower lock plate
	10	0.34 in (8.7 mm)	BVS4-10-LP-RK	

Ball Valve without Handle

- Ball Valve without handle can be directly connected to the FITOK actuator assembly.
- To order, please add -AM to the valve ordering number.
Example: BVSS-FL4-05-AM



Locking Device 1



Locking Device 2

B-66 Ball Valves

Series	Body Material	Connection 1 Type	Connection 1 Size	Connection 2/3 Type	Connection 2/3 Size	Seat Material	Orifice Size	Handle/Actuator	For Actuator	Flow Pattern	Locking Device	Special Application	Cleaning and Packaging
BV	SS CF8M	FNS Female NPT	2 1/8"	Same as Connection 1 Specified in the same way as Connection 1 type and size	PTFE K PCTFE P PEEK	02 0.09" (2.4 mm) 03 0.13" (3.2 mm) 04 0.17" (4.2 mm) 05 0.19" (4.7 mm) 06 0.25" (6.4 mm) 10 0.41" (10.3 mm)	Black Nylon Handle Red Nylon Handle GR Green Nylon Handle J Blue Nylon Handle Y Yellow Nylon Handle U Black Aluminium Handle AM Without Handle C 90° Normally Closed Pneumatic Actuator	None H Mechanical Limit Switch N Inductive Limit Switch Q Solenoid Valve HQ Mechanical Limit Switch and Solenoid Valve NQ Inductive Limit Switch and Solenoid Valve	No L Locking Device 1 LP Locking Device 2	Straight A Angle (Bottom Port Inlet) 3 3-Way (Diverter Valve)	None S NACE MR0175 CE CE Certification		
	6L CF3M	NS Male NPT	3 3 mm										
	S4 CF8	FRT Female BSPT	4 1/4"										
	B Brass	RT Male BSPT	5 5/16"										
		FMS Female Metric Thread (for RG-M)	6 3/8" or 6 mm or M6 x 1										
		MS Male Metric Thread (for RG-M)	8 1/2" or 8 mm										
		FRP Female BSPP (For RP)	10 10 mm or M10 x 1										
		BP Male BSPP (For RG)	12 3/4" or 12 mm										
		FL Fractional Tube Fitting	14 14 mm or M14 x 1.5										
		ML Metric Tube Fitting	16 16 mm										
		UFB Rotatable Fractional Tube Butt Weld	18 18 mm										
		UMB Rotatable Metric Tube Butt Weld	20 20 mm or M20 x 1.5										
		UPB Rotatable Pipe Butt Weld	22 22 mm or M22 x 1.5										
			24 M24 x 1.5										

Note: "Ordering Number Description" is a reference to understand the combination rules of FITOK product part number. Not all combinations are available.

- Standard thread pitch for metric threads are as follows:
M10 and below: 1 mm
M12 to M24: 1.5 mm
Standard thread pitch should be omitted in the ordering number, others should be specified.
- For oxygen-enriched environment or hazardous media service, contact FITOK Group or our authorized distributors.
- Cleaning and Packaging:
FC-01: Standard cleaning and packaging for general industrial procedures.
FC-02: Special cleaning and packaging for wetted system components to ensure compliance with product cleaning requirement of ASTM G93 Level C.
- For more information about pneumatic actuator ball valves, please refer to the catalog Actuated Ball Valves.
- Inert Silicon Coating: Except for ball valves with PEEK seat, wetted metal components

FC-01	FC-02
-------	-------

6. CE certification is available. For more information, please contact FITOK group or our authorized distributors

High Temperature Metal-Seated Ball Valves

BK Series

Features

- Working pressures up to 1,000 psig (69 bar)
- Working temperature: -65°F to 662°F (-54°C to 350°C)
- Suitable for high-temperature and high-viscosity liquid media
- Floating ball design paired with disc-spring-loaded metal seats to compensate for seat wear and pressure/temperature changes, improving leak-tight integrity
- Blowout-proof stem minimizes failures caused by stem movement or looseness
- Each valve meets FCI 70-2 Class VI low pressure gas tightness and ISO 5208 Rate D high pressure liquid test requirements




Ball Valves
Plug Valves

Technical Data

Orifice, in. (mm)	0.5 (12.7), 1 (25.4)	
Material	316/304 SS	
Connection Type	FITOK Tube Fitting	Weld Fitting
Temperature, °F (°C)	-65 (-54) to 662 (350)	
Working Pressure, psig (bar)	1000 (69)	

Standard Materials of Construction




Item	Component	Material	
1	Body	CF8M/A351	CF8/A351
2	Flange Seal	Graphite	
3	Seat	316 SS/A479, hardfacing stellite	304 SS/A479, hardfacing stellite
4	Disc Spring	A75	
5	End Connection	CF8M/A351	CF8/A351
6	Ball	316/304 SS, HVOF-sprayed Cr3C2/NiCr coatings	
7	Hex Bolt (Full Thread)	Stainless Steel	
8	Stem Bearing	Stellite 6/A479	
9	Stem Washer	316 SS /A479	
10	Packing	Graphite	
11	Stem	316 SS/A479	
12	Stem Spring	Strain-hardened 316 SS/A240	
13	Hex Nut	Stainless Steel	
14	Stop Plate	304 SS/A240	
15	Handle	304 SS/A240	

Note: Wetted components are listed in italics. For other materials, please contact FITOK Group or our authorized distributors.

Dimensions


Dimensions are for reference only and are subject to change.



Basic Ordering Information	Connection Type		Orifice in. (mm)	Dimensions, in. (mm)			
	Connection 1	Connection 2		A	B	C	D
BK□□-FL8-13G	1/2" FITOK	1/2" FITOK	0.41 (10.4)	3.79 (96.2)	0.89 (22.7)	2.25 (57.1)	6.5 (165)
BK□□-FL10-13G	5/8" FITOK	5/8" FITOK	0.5 (12.7)	3.79 (96.2)	0.89 (22.7)	2.25 (57.1)	6.5 (165)
BK□□-FL12-13G	3/4" FITOK	3/4" FITOK		3.92 (99.6)	0.89 (22.7)	2.25 (57.1)	6.5 (165)
BK□□-ML16-13G	16 mm FITOK	16 mm FITOK		3.92 (99.6)	0.89 (22.7)	2.25 (57.1)	6.5 (165)
BK□□-ML18-13G	18 mm FITOK	18 mm FITOK		3.91 (99.4)	0.89 (22.7)	2.25 (57.1)	6.5 (165)
BK□□-TB12-13G	3/4" x 0.120" Tube Butt Weld	3/4" x 0.120" Tube Butt Weld		3.8 (96.6)	0.89 (22.7)	2.25 (57.1)	6.5 (165)
BK□□-TS12-13G	3/4" Tube Socket Weld	3/4" Tube Socket Weld		3.2 (80.2)	0.89 (22.7)	2.25 (57.1)	6.5 (165)
BK□□-PB8-13G	1/2 x SCH80 Pipe Butt Weld	1/2 x SCH80 Pipe Butt Weld		3.24 (82.34)	0.89 (22.7)	2.25 (57.1)	6.5 (165)
BK□□-PB12-13G	3/4 x SCH80 Pipe Butt Weld	3/4 x SCH80 Pipe Butt Weld		3.24 (82.34)	0.89 (22.7)	2.25 (57.1)	6.5 (165)
BK□□-TB24-25G	1 1/2" x 0.197" Tube Butt Weld	1 1/2" x 0.197" Tube Butt Weld	1 (25.4)	—	—	—	—
BK□□-TS20-25G	1 1/4" Tube Socket Weld	1 1/4" Tube Socket Weld		—	—	—	—
BK□□-PB20-25G	1 1/4 x SCH80 Pipe Butt Weld	1 1/4 x SCH80 Pipe Butt Weld		—	—	—	—

1. Connection type of "FITOK" means FITOK double ferrule tube fittings.
2. Sizes and types listed are standard. Other sizes and types are available upon request. For details, please contact FITOK Group or our authorized distributors.
3. Dimensions are shown with FITOK tube fitting nuts finger-tight. For dimensions not shown above, please contact FITOK Group or our authorized distributors.

Ordering Number Description



1. If you need a port with orbital welding, please contact FITOK Group.


Note: "Ordering Number Description" is a reference to understand the combination rules of FITOK product part number. Not all combinations are available.

Alternative Fuel Service (AFS) Ball Valves

BU Series

Features

- ⦿ Working pressures up to 6,000 psig (414 bar)
- ⦿ Working temperature: -40 to 250°F (-40 to 121°C)
- ⦿ Cv up to 13.8
- ⦿ No packing adjustment required
- ⦿ Field repairable with seal kit
- ⦿ Floating ball design paired with disc-spring-loaded seats to compensate for seat wear and pressure/temperature changes, improving leak-tight integrity
- ⦿ Each valve is factory leak-tested with nitrogen or compressed air at rated pressure
- ⦿ Available with ECE R110 type approval




Pressure VS Temperature Ratings

End Connection	FITOK Tube Fitting			Female Pipe	
	3/8, 1/2 in., 12 mm	3/4 in., 16 mm	1 in.	3/8, 1/2 in.	3/4 in.
Temperature °F (°C)	Working Pressure, psig (bar)				
-40 (-40) ~ 250 (121)	6000 (414)	5800 (400)	4700 (324)	6000 (414)	6000 (414)

Note: Ratings are based on valves of standard materials.

Standard Materials of Construction




Item	Component	Material/ASTM Specification
1	Handle	Nylon with stainless steel insert
2	Set screw	Zinc-plated carbon steel
3	<i>Guide ring</i>	<i>PTFE/D1710</i>
4	<i>Stem</i>	<i>316 SS/A479</i>
5	<i>Packing bolt</i>	<i>316 SS/A479</i>
6	<i>Stem backup ring</i>	<i>PEEK</i>
7	Lock nut	316 SS/A479
8	<i>Stem O-ring</i>	<i>Low-temperature fluorocarbon</i>
9	<i>Packing bolt washer</i>	<i>Silver-plated 316 SS/A269</i>
10	<i>Thrust washer</i>	<i>PEEK</i>
11	<i>Coned-disc spring</i>	<i>316 SS/A240</i>
12	<i>Seat gland</i>	<i>316 SS/A479</i>
13	<i>Seat backup ring</i>	<i>PTFE/D1710</i>
14	<i>Seat O-ring</i>	<i>Low-temperature fluorocarbon</i>
15	<i>Seat</i>	<i>PEEK</i>
16	<i>End connection gasket</i>	<i>Silver-plated 316 SS/A269</i>
17	<i>Ball</i>	<i>316 SS/A479</i>
18	<i>Body</i>	<i>316 SS/A479</i>
19	<i>End connection</i>	<i>316 SS/A479</i>
<i>Lubricant</i>		<i>PTFE-based</i>

Note: Wetted components listed in italics.

Dimensions

Dimensions in in. (mm) are for reference only and subject to change.



Ordering Number	Connection ^① Type and Size	Cv	Orifice in. (mm)	Dimensions in. (mm)	
				A	B
BUSS-ML10-P12	10 mm FITOK	4.2	0.31 (7.9)	4.21 (107)	2.11 (53.5)
BUSS-ML12-P12	12 mm FITOK	5.2	0.41 (10.3)	4.42 (112.2)	2.21 (56.1)
BUSS-ML16-P12	16 mm FITOK	12.4	0.47 (12.0)	4.42 (112.3)	2.21 (56.2)
BUSS-FL6-P12	3/8" FITOK	4.0	0.28 (7.1)	4.20 (106.6)	2.10 (53.3)
BUSS-FL8-P12	1/2" FITOK	7.2	0.41 (10.3)	4.40 (111.8)	2.20 (55.9)
BUSS-FL12-P12	3/4" FITOK	7.1	0.47 (12.0)	4.50 (114.3)	2.46 (62.5)
BUSS-FL16-P12	1" FITOK	6.5	0.47 (12.0)	4.93 (125.1)	2.25 (57.1)
BUSS-FNS6-P12	3/8" Female NPT	11.0	0.47 (12.0)	4.01 (102)	2.00 (50.8)
BUSS-FNS8-P12	1/2" Female NPT	13.8		4.01 (102)	2.00 (50.8)
BUSS-FNS12-P12	3/4" Female NPT	7.8		4.13 (105)	2.06 (52.3)
BUSS-FRT8-P12	1/2" Female BSPT	13.8		4.01 (102)	2.00 (50.8)

Note: Dimensions shown with FITOK tube fitting nuts finger-tight. Valves can be ordered with two different end connections. Contact FITOK Group or our authorized distributors. Not recommended for panel mounting; not available with pneumatic actuator.

CNG/NGV Application

ECE R110 Manual Service Valve Type Approval

Classification: Class 0

Temperature: -40 to 248°F (-40 to 120°C)

Pressure: 3770 psig (260 bar)

To order, add **-R110** to the valve ordering number.

Example: BUSS-ML12-P12-**R110**

Seal kit for field replacement is available, see "Seal Kits".

Seal Kits

Seal Kit Name	Seal Kit Ordering Number	Seal Kit Content
Seat seal kit	SS-BU-P-SE	Seat, seat backup ring, seat O-ring, coned-disc spring, end connection gasket, instructions.
Stem and seat seal kit	SS-BU-P	Guide ring, stem backup ring, stem O-ring, packing bolt washer, thrust washer, seat, seat backup ring, seat O-ring, coned-disc spring, end connection gasket, instructions

Locking Device

Locking Device 1

- ⦿ Locks BU series valves, featuring a locking hole diameter of 0.21 in (5.2 mm).
- ⦿ To order a ball valve with Locking Device 1, add - **L** to the valve ordering number.
Example: BUSS-ML12-P12- **L**

Locking Device 2

- ⦿ Locks BU series valves, featuring a locking hole diameter of 0.34 in (8.7 mm).
- ⦿ To order a ball valve with Locking Device 2, add - **LP** to the valve ordering number.
Example: BUSS-ML12-P12-**LP**
- ⦿ No impact on panel mounting.
- ⦿ Locking device kits are also available for individual purchase to add locking functionality to your existing standard manual ball valves, with ordering information as follows:

Locking Device 2 Kits

Name	Kit Ordering Number	Content
Locking Device Kits	BU54-12-LP-RK	Upper lock plate, lower lock plate, handle, hexagon socket set screws



Locking Device 1



Locking Device 2

Ball Valve without Handle

- ⦿ Ball Valve without handle can be directly connected to the FITOK actuator assembly.
- ⦿ To order, please add -**AM** to the valve ordering number.
Example: BUSS-FL8-P12-**AM**

Ordering Number Description

BUSS – ML12 – FL12 – P12 – OHQL – SF2

Series	Body Material	Connection 1 Type	Connection 1 Size	Connection 2 Type	Connection 2 Size	Seat Material	Orifice Size	Handle/Actuator	Actuator	Locking Device	Special Application	Cleaning and Packaging
BU	SS	316 SS	FNS Female NPT	6	3/8"	P PEEK	12 0.472" (12.0 mm) Max.	Black Nylon Handle	None	No	None	FC-01
			FRT Female BSPT	8	1/2"			I Red Nylon Handle	H Mechanical Limit Switch	L Locking Device 1	R110 ECE R110	F2 FC-02
			RT Male BSPT	10	10 mm			GR Green Nylon Handle	N Inductive Limit Switch	LP Locking Device 2	S NACE MR0175	
			FL Fractional Tube Fitting	12	3/4" or 12 mm			J Blue Nylon Handle	Q Solenoid Valve			
			ML Metric Tube Fitting	16	1" or 16 mm			U Black Aluminum Handle	HQ Mechanical Limit Switch and Solenoid Valve	NQ Inductive Limit Switch and Solenoid Valve		
								AM Without Handle				
								C 90° Normally Closed Pneumatic Actuator				
								O 90° Normally Open Pneumatic Actuator				
								D 90° Double Acting Pneumatic Actuator				

Note: "Ordering Number Description" is a reference to understand the combination rules of FITOK product part number. Not all combinations are available.

- Standard thread pitch for metric threads are as follows:
M10 and below: 1 mm
M12 to M24: 1.5 mm
Standard thread pitch is omitted in ordering number.
For special thread pitch, specify in the ordering number.
- For oxygen-enriched environment or hazardous media service, contact FITOK Group or our authorized distributors.
- Cleaning and Packaging:
FC-01: Standard cleaning and packaging for general industrial procedures.
FC-02: Special cleaning and packaging for wetted system components to ensure compliance with product cleaning requirement of ASTM G93 Level C.
- For more details about ball valves with pneumatic actuators, refer to Actuated Ball Valves.
- Certifications do not include attachments to the valve, such as actuators or a different handle mechanism.